

DLAH-12D3



- ✦ Pluggable surge protection for «DIN» mounting
- ✦ Coordination inductor
- ✦ Up to 2.4 A line current
- ✦ Remote supply version
- ✦ All types of Telephone and Data lines
- ✦ Shield wire protection
- ✦ IEC 61643-21 compliance



	Electrical Characteristics																																							
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube L: Inductor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RS232, RS485</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>12 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>15 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>2.4 A</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 µs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td></td> <td>10 µH</td> </tr> <tr> <td>Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)</td> <td>Up</td> <td>30 V</td> </tr> <tr> <td>Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)</td> <td>Up</td> <td>20 V</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>In L/L</td> <td>5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category</td> <td>In L/PE</td> <td>5 kA</td> </tr> </table>	Network		RS232, RS485	Nominal line voltage	Un	12 V	Max. DC operating voltage	Uc	15 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	2.4 A	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA	Line inductance (± 10 %)		10 µH	Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	30 V	Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	20 V	Impulse current 2 x 10/350µs Test - D1 Category	Iimp	5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	5 kA
Network		RS232, RS485																																						
Nominal line voltage	Un	12 V																																						
Max. DC operating voltage	Uc	15 Vdc																																						
Max. frequency	f max.	> 3 MHz																																						
Insertion loss		< 1 dB																																						
Max. load current @25°C	IL	2.4 A																																						
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA																																						
Line inductance (± 10 %)		10 µH																																						
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	30 V																																						
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	20 V																																						
Impulse current 2 x 10/350µs Test - D1 Category	Iimp	5 kA																																						
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																						
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	5 kA																																						
	Mechanical Characteristics																																							
	<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+TVS diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal: cross section 0.4-1.5mm²</td> </tr> <tr> <td>Format</td> <td></td> <td>Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>DLAHH-12D3</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> </table>	Technology		GDT+TVS diode	SPD configuration		1-pair+shielded	Connection to Network		By screw terminal: cross section 0.4-1.5mm ²	Format		Plug-in DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Spare module(s)		DLAHH-12D3	Dimensions		See diagram			
Technology		GDT+TVS diode																																						
SPD configuration		1-pair+shielded																																						
Connection to Network		By screw terminal: cross section 0.4-1.5mm ²																																						
Format		Plug-in DIN box																																						
Mounting		Symmetrical rail 35 mm (EN 60715)																																						
Housing material		Thermoplastic UL94 V-0																																						
Operating temperature	Tu	-40/+85°C																																						
Protection rating		IP20																																						
Failsafe mode		Short-circuit																																						
Disconnection indicator		Transmission interrupt - default mode 2																																						
Spare module(s)		DLAHH-12D3																																						
Dimensions		See diagram																																						
	Standards																																							
	<table border="1"> <tr> <td>Standards compliance</td> <td></td> <td>IEC 61643-21 / EN 61643-21 / UL497B</td> </tr> </table>	Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B																																				
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B																																						
	Part number																																							
	<table border="1"> <tr> <td>641002</td> </tr> </table>	641002																																						
641002																																								