

## DLAW-12D3



- ✦ Din rail plug-in surge protector
- ✦ 1-pair
- ✦ Un: 12 V
- ✦ Shield wire protection
- ✦ Plug-out with line cut-off
- ✦ IEC 61643-21 compliance
- ✦ UL497B



	<b>Electrical Characteristics</b>																																														
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr><td>Network</td><td></td><td>RS232, RS485</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>12 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>15 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>&gt; 3 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>&lt; 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>300 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Line inductance (± 10 %)</td><td></td><td>non</td></tr> <tr><td>Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)</td><td>Up</td><td>30 V</td></tr> <tr><td>Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</td><td>Up</td><td>20 V</td></tr> <tr><td>Impulse current 2 x 10/350μs Test - D1 Category</td><td>Iimp</td><td>5 kA</td></tr> <tr><td>Line/Line Nominal discharge current C2 Category</td><td>In L/L</td><td>5 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category</td><td>In L/PE</td><td>5 kA</td></tr> <tr><td>Line resistance</td><td></td><td>&lt; 4.7 Ohm</td></tr> <tr><td>Line resistance (± 10%)</td><td></td><td>4.7 Ohm</td></tr> </table>		Network		RS232, RS485	Nominal line voltage	Un	12 V	Max. DC operating voltage	Uc	15 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance (± 10 %)		non	Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up	30 V	Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up	20 V	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	5 kA	Line resistance		< 4.7 Ohm	Line resistance (± 10%)		4.7 Ohm
Network		RS232, RS485																																													
Nominal line voltage	Un	12 V																																													
Max. DC operating voltage	Uc	15 Vdc																																													
Max. frequency	f max.	> 3 MHz																																													
Insertion loss		< 1 dB																																													
Max. load current @25°C	IL	300 mA																																													
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																													
Line inductance (± 10 %)		non																																													
Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up	30 V																																													
Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up	20 V																																													
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA																																													
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																													
Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	5 kA																																													
Line resistance		< 4.7 Ohm																																													
Line resistance (± 10%)		4.7 Ohm																																													
	<b>Mechanical Characteristics</b>																																														
	<table border="1"> <tr><td>Disconnection</td><td></td><td>Specific version with line cut-off in case of removal plug-in module</td></tr> <tr><td>Technology</td><td></td><td>GDT+TVS diode</td></tr> <tr><td>SPD configuration</td><td></td><td>1-pair+shielded</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal: cross section 0.5-2.5mm<sup>2</sup></td></tr> <tr><td>Format</td><td></td><td>Plug-in DIN box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit</td></tr> <tr><td>With line cut-off in case of removal plug-in module</td><td></td><td>Yes</td></tr> <tr><td>Disconnection indicator</td><td></td><td>Transmission interrupt - default mode 2</td></tr> <tr><td>Spare module(s)</td><td></td><td>DLAM-12D3</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> </table>		Disconnection		Specific version with line cut-off in case of removal plug-in module	Technology		GDT+TVS diode	SPD configuration		1-pair+shielded	Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>	Format		Plug-in DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit	With line cut-off in case of removal plug-in module		Yes	Disconnection indicator		Transmission interrupt - default mode 2	Spare module(s)		DLAM-12D3	Dimensions		See diagram			
Disconnection		Specific version with line cut-off in case of removal plug-in module																																													
Technology		GDT+TVS diode																																													
SPD configuration		1-pair+shielded																																													
Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>																																													
Format		Plug-in DIN box																																													
Mounting		Symmetrical rail 35 mm (EN 60715)																																													
Housing material		Thermoplastic UL94 V-0																																													
Operating temperature	Tu	-40/+85°C																																													
Protection rating		IP20																																													
Failsafe mode		Short-circuit																																													
With line cut-off in case of removal plug-in module		Yes																																													
Disconnection indicator		Transmission interrupt - default mode 2																																													
Spare module(s)		DLAM-12D3																																													
Dimensions		See diagram																																													
	<b>Standards</b>																																														
	Standards compliance IEC 61643-21 / EN 61643-21 / UL497B																																														
	<b>Part number</b> 640802																																														