



G: Gas discharge tube
V: Varistor
D: Clamping diode network
LED: Indicator

Electrical Characteristics		
Network		12 Vac/Vdc
AC system		TT-TN
Max. DC operating voltage	Uc	15 Vac/Vdc
Max. frequency	f max.	16 MHz
Insertion loss		< 0.1 dB
Max. load current @25°C	IL	300 mA
Max. load current @25°C	IL	5 A
Nominal discharge current 15 x 8/20 µs impulses	In	5 kA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	10 kA
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	10 kV / 5 kA
Protection mode(s)		Common/Differential mode
Protection level @ In (8/20µs)	Up	0.22 kV
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	0.22 kV
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	0.22 kV
ELEC		
Network		Signal video
ELEC		
Max. DC operating voltage	Uc	6 Vdc
ELEC		
Max. frequency	f max.	16 MHz
ELEC		
Insertion loss		< 1dB
ELEC		
Nominal discharge current 15 x 8/20 µs impulses	In	5 kA
ELEC		
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	10 kA
ELEC		
Protection level @ In (8/20µs)	Up	20 V
ELEC		
Network		2 pairs signal 0-5 V
ELEC		
Max. DC operating voltage	Uc	8 Vdc
ELEC		
Max. frequency	f max.	16 MHz
ELEC		
Insertion loss		< 1dB
ELEC		
Nominal discharge current 15 x 8/20 µs impulses	In	2.5 kA
ELEC		
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	5 kA
ELEC		
Protection level @ In (8/20µs)	Up	20 V
Mechanical Characteristics		
Technology		MOV+GDT
Connection to Network		By screw terminals: 2.5mm² max.
Format		DIN rail or flange
Mounting		DIN rail or plate (flange)
Housing material		Anodized aluminum
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Green LED OFF and line cut-off
Disconnection indicator		LED green OFF and AC network cut-off
Dimensions		See diagram
Standards		

Standards compliance	IEC 61643-21 / EN 61643-21
Part number	
420433	