




- ✦ Security camera surge protector
- ✦ AC + Cat.5 (connector RJ45)
- ✦ Compact aluminium housing
- ✦ Rail DIN mounting or plate



Electrical Characteristics		
Network		120 V single-phase
Max. DC operating voltage	Uc	150 Vdc
Max. load current @25°C	IL	5 A
Nominal discharge current 15 x 8/20 µs impulses	In	5 kA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	10 kA
Protection mode(s)		Common/Differential mode
Protection level @ In (8/20µs)	Up	0.8 kV
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	0.8 kV
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	0.8 kV
Mechanical Characteristics		
Technology		MOV+GDT
Connection to Network		By screw terminals: 2.5mm ² max.
Format		DIN rail or flange
Mounting		DIN rail or plate (flange)
Housing material		Anodized aluminum
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection and Power cut off
Disconnection indicator		Green LED OFF and line cut off
Dimensions		See diagram
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21
Part number		
420414		