




CITEL

DC power surge protector Type 2 -220 Vdc

DCC40C-20-275



- Type 2 DC power surge protector
- Compact design
- I_{max}: 40 kA
- Pluggable module
- Remote signaling (option)
- Low Up protection level
- Compliance prIEC 61643-41 and UL1449 ed.5



| Electrical Characteristics | | |
|---|------------------|--|
| SPD type | IEC | 2 |
| Network | | DC network 220 Vdc |
| Nominal PV voltage | Uocstc | 220 Vdc |
| Max. AC operating voltage | Uc | 210 Vac |
| Max. PV operating voltage | Ucpv | 275 Vdc |
| Max. DC operating voltage | Uc | 275 Vdc |
| Max. load current @25°C | IL | 20 A |
| Residual Current Leakage current to Ground | Ipe | < 0.2 mA |
| PV Permanent Operating current Current consumption at Ucpv | Icpv | < 0.1 mA |
| Nominal discharge current 15 x 8/20 μs impulses | In | 20 kA |
| Max. discharge current max. withstand @ 8/20 μs by pole | I _{max} | 40 kA |
| Current withstand short circuit PV | Iscpv | 1000 A |
| Connection mode(s) | | +/-/PE |
| Protection level +/-PE (-/PE) @ In (8/20μs) | Up | 900 V |
| Mechanical Characteristics | | |
| Technology | | MOV |
| Connection to Network | | By screw terminals: 1.5-10mm ² (actives wires) and 2.5-25mm ² (ground) |
| Format | | Plug-in modular box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection from DC network |
| Disconnection indicator | | 1 mechanical indicator - Red/Green |
| Spare module(s) | | MDDC40C-20-275 |
| Remote signaling of disconnection | | Option DDC40CS-20-275 : output on changeover contact |
| Dimensions | | See diagram - 1TE (EN43880) |
| Weight | | 0.140 kg |
| Disconnectors | | |
| Thermal disconnector | | Internal |
| Back-up protection device | | 50 A min. - 125 A max. - Fuses Type gG |
| Standards | | |
| Standards compliance | | prIEC 61643-41 and UL1449 ed.5 |
| Part number | | |
| 828410911 | | |

