




CITEL

DC power surge protector

DDC50-21Y-1500



- DC power Type 2 SPD
- For Energy Storage/EV Charging
- In/Imax: 20/50 kA
- Pluggable modules
- Remote signaling (option)
- prIEC 61643-41 compliance



Electrical Characteristics

SPD type	IEC	2
Nominal DC voltage	Un-dc	1200 Vdc
Max. DC operating voltage	Uc	1500 Vdc
Residual Current Leakage current to Ground	Ipe	< 0.2 mA
Nominal discharge current 15 x 8/20 μs impulses	In	20 kA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	50 kA
Impulse current by pole max. withstand 10/350 μs by pole	Iimp	4 kA
Protection level +/- @ In (8/20 μs)	Up	5.1 kV
Protection level +/-PE (-/PE) @ In (8/20 μs)	Up	5.1 kV
Admissible short-circuit current	Iscsr	100 000 A

Mechanical Characteristics

Connection to Network	By screw terminals: 2.5-25 mm ² (35 mm ² rigid)
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from DC network
Disconnection indicator	1 mechanical indicator by pole - Red/Green
Spare module(s)	MDDC50-1500
Remote signaling of disconnection	option DDC50S-21Y-1500: output on changeover contact
Dimensions	See diagram - 3 TE (EN43880)
Weight	0.345 kg

Disconnectors

Thermal disconnector	Internal
Back-up protection device	Fuse assembly: SFD50S-10-1500DC /or 50 A min. (Iscsr 100 kA) - 125 A max. (Iscsr 50 kA) - gBat Fuses

Standards

Standards compliance	prIEC 61443-41 - IEC61643-11
----------------------	------------------------------

Part number

828511653

