

### SFD1-13



- ✦ Specific Fuses (SPD Fusing Disconnectors) for short circuit protection of Type 1 AC surge protectors
- ✦ Surge current withstand: 12.5 kA @ 10/350µs
- ✦ 10 units per packaging
- ✦ Very compact
- ✦ Fusion signaling feature
- ✦ Remote signaling though fuse holder



Electrical Characteristics		
Max. AC operating voltage	Uc	500 Vac
Nominal discharge current 15 x 8/20 µs impulses	In	50 kA
Max. discharge current max. withstand @ 8/20 µs by pole	I <sub>max</sub>	80 kA
Impulse current by pole max. withstand 10/350µs by pole	I <sub>imp</sub>	12.5 kA
Equivalent rated AC current		125 A
Breaking capacity		100 000 A
Fusing indicator		Yes
Remote fusing indication		Through dedicated fuse holder
Residual voltage	Up	< 0.4 kV @ 12.5 kA
Mechanical Characteristics		
Format		Cylindrical
Mounting		On cylindrical fuse holder
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Number of units per package		10 units per packaging
Dimensions		14x51 mm
Associate Fuse holder		BSFD14-10S & SFD1-13 1 pole BSFD14-11S* & SFD1-13 single phase (L+N) BSFD14-20S & SFD1-13 2-phase BSFD14-30S & SFD1-13 3-phase BSFD14-31S* & SFD1-13 3-phase+N BSFD14-40S & SFD1-13 4-phase *The Neutral position is equipped with a non-fusing element The fuse holders are all equipped with a remote signaling
Standards		
Standards compliance		EN 61643-11 /IEC 61643-11 /EN 60269-1/EN 60269-2/IEC 60269-1/IEC 60269-2
Part number		
39466		