

DLAS1-48D3



- ✦ 1-pair Pluggable SPD for dataline
- ✦ Visual indicator in failsafe behaviour
- ✦ Without line cut-off
- ✦ Line voltage 48 Vdc
- ✦ Din rail mounting, Screw terminals
- ✦ IEC/EN 61643-21 and UL497B compliance



	Electrical Characteristics																																							
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube PTC: Thermal resistor R: Resistor D: Clamping diode Vi: Indicator</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RNIS-T0, 48 V line</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>48 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>53 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 µs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td></td> <td>non</td> </tr> <tr> <td>Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)</td> <td>Up</td> <td>70 V</td> </tr> <tr> <td>Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)</td> <td>Up</td> <td>70 V</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>In L/L</td> <td>5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category</td> <td>In L/PE</td> <td>5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>4.7 Ohm</td> </tr> </table>	Network		RNIS-T0, 48 V line	Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Max. frequency	f max.	> 3 MHz	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA	Line inductance (± 10 %)		non	Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	70 V	Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	70 V	Impulse current 2 x 10/350µs Test - D1 Category	Iimp	5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	5 kA	Line resistance (± 10%)		4.7 Ohm
Network		RNIS-T0, 48 V line																																						
Nominal line voltage	Un	48 V																																						
Max. DC operating voltage	Uc	53 Vdc																																						
Max. frequency	f max.	> 3 MHz																																						
Max. load current @25°C	IL	300 mA																																						
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA																																						
Line inductance (± 10 %)		non																																						
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	70 V																																						
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	70 V																																						
Impulse current 2 x 10/350µs Test - D1 Category	Iimp	5 kA																																						
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																						
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	5 kA																																						
Line resistance (± 10%)		4.7 Ohm																																						
	Mechanical Characteristics																																							
	<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+Clamping diode+PTC (thermal resistor) + Resistor</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td></td> <td>Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Opening line - transmission cut-off - fault mode 2</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>Visual indicator is red</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>DLAS1M-48D3</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> </table>	Technology		GDT+Clamping diode+PTC (thermal resistor) + Resistor	SPD configuration		1-pair+shielded	Connection to Network		By screw terminal: cross section 0.5-2.5mm ²	Format		Plug-in DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Opening line - transmission cut-off - fault mode 2	Disconnection indicator		Visual indicator is red	Spare module(s)		DLAS1M-48D3	Dimensions		See diagram			
Technology		GDT+Clamping diode+PTC (thermal resistor) + Resistor																																						
SPD configuration		1-pair+shielded																																						
Connection to Network		By screw terminal: cross section 0.5-2.5mm ²																																						
Format		Plug-in DIN box																																						
Mounting		Symmetrical rail 35 mm (EN 60715)																																						
Housing material		Thermoplastic UL94 V-0																																						
Operating temperature	Tu	-40/+85°C																																						
Protection rating		IP20																																						
Failsafe mode		Opening line - transmission cut-off - fault mode 2																																						
Disconnection indicator		Visual indicator is red																																						
Spare module(s)		DLAS1M-48D3																																						
Dimensions		See diagram																																						
	Standards																																							
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B																																						
Part number		6415041																																						