






- ✦ High current data transmission
- ✦ Common mode and differential mode protection
- ✦ Data lines, including those isolated from Earth
- ✦ Compact DIN rail enclosure, high density protection
- ✦ Protection of shield wire
- ✦ Location and test categories: D1, C2, C3
- ✦ IEC 61643-21 compliance



G: 3-electrode gas tube
Gb: 2-electrode gas tube
R: Resistor
D: Clamping diode



Electrical Characteristics

Network		4-20mA
Nominal line voltage	Un	24 V
Max. DC operating voltage	Uc	32 Vdc
Cut-off frequency -3dB, 100 ohm system	f max.	> 75 MHz
Insertion loss		< 1 dB
Max. load current @25°C	IL	600 mA
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	20 kA
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	60 V
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	650 V
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA
Nominal discharge current C2 Category	I _n	10 kA
Line resistance (± 10%)		2 Ohm

Mechanical Characteristics

Technology		GDT+TVS diode
SPD configuration		1-pair+shielded
Connection to Network		By screw terminal: cross section 0.5-2.5mm ²
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit
Disconnection indicator		Transmission interrupt - default mode 2
Spare module(s)		DLAM-24D2
Dimensions		See diagram
Weight		0.063 kg

Standards

Standards compliance		IEC 61643-21 / EN 61643-21
----------------------	--	----------------------------

Part number

Part number		6401631
-------------	--	---------