






# CITEL

## Compact single-phase type 2 (or 3) surge protector - Monobloc

### DACN15-P11-275/INV



- ✦ Type 2 or 3 surge protectors with bottom connection
- ✦ Compact Single-phase
- ✦ In: 5 kA
- ✦ I<sub>max</sub>: 15 kA
- ✦ Commun/Differential mode
- ✦ Monobloc module
- ✦ EN 61643-11, IEC 61643-11, and UL1449 ed.5 compliance



V: High-energy varistor  
 GSG: Specific Gas Tube  
 Ft: Thermal fuse  
 t\*: Thermal disconnection system  
 MI: Disconnection indicator

Electrical Characteristics			
SPD type	IEC	2 (or 3)	
Network		230/400 V	
AC system		TT-TN	
Max. AC operating voltage	U <sub>c</sub>	275 Vac	
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	
Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT	1200 V/300A/200 ms withstand	
Residual Current Leakage current to Ground	I <sub>pe</sub>	None	
Follow current	I <sub>f</sub>	None	
Nominal discharge current 15 x 8/20 μs impulses	I <sub>n</sub>	5 kA	
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	15 kA	
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	U <sub>oc</sub>	10 kV	
Protection mode(s)		L/N and N/PE	
Protection level L/N @ I <sub>n</sub> (8/20μs)	U <sub>p</sub> L/N	1.1 kV	
Protection level N/PE @ I <sub>n</sub> (8/20μs)	U <sub>p</sub> N/PE	1.5 kV	
Admissible short-circuit current	I <sub>sc</sub>	10 000 A	
Mechanical Characteristics			
Technology		MOV+GDT	
SPD configuration		Single phase	
Connection to Network		Bottom connection, by screw terminals: 1.5-10mm <sup>2</sup>	
Format		Monobloc modular box	
Mounting		Symmetrical rail 35 mm (EN 60715)	
Housing material		Thermoplastic UL94 V-0	
Operating temperature	T <sub>u</sub>	-40/+85°C	
Protection rating		IP20	
Failsafe mode		Disconnection from AC network	
Disconnection indicator		Green LED OFF	
Dimensions		See diagram - 1TE (EN43880)	
Weight		0.093 kg	
Disconnectors			
Thermal disconnector		Internal	
Installation ground fault breaker		Type 'S' or delayed	
Back-up protection device		20 A min. - 125 A max. - Fuses type gG	
Standards			
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5	
Part number			
70146023			

