





- SPD Specific Disconnectors (SSD) for short circuit protection of Type 2 AC surge protectors
- Surge current withstand: 40 kA @ 8/20 $\mu$ s
- Wide range of short circuit current protected
- Reusable after switch triggered
- Low rated tripping current with time-current characteristics for overcurrent coordination with upstream OCPD and safety disconnect in case of SPD failure



#### Electrical Characteristics

Minimum delay tripping current	$I_d$	3A@<5s
Minimum instantaneous tripping current	$I_i$	5A@<0.1s
Rated impulse withstand voltage	$U_{imp}$	4 kV
Nominal line voltage	$U_n$	230/400 Vac
Nominal discharge current 15 x 8/20 $\mu$ s impulses	$I_n$	20 kA
Max. discharge current max. withstand @ 8/20 $\mu$ s by pole	$I_{max}$	40 kA
Equivalent rated AC current		63 A
Breaking capacity		100 000 A
Residual voltage	$U_p$	< 2.3 kV (+SPD)
Rated insulation voltage	$U_i$	400 Vac

#### Mechanical Characteristics

Format		Monobloc modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Operating temperature	$T_u$	-40/+85°C
Protection rating		IP20
Remote signaling of disconnection		Output on changeover contact
Wiring for remote signaling		0.75 mm <sup>2</sup> max.
Max. Voltage/Current for remote signaling		240 V / 2 A (AC) , 24 V / 6 A (DC)
Remote signaling of disconnection via control module		With attached separated module
Dimensions		See diagram - 1TE (EN43880)

#### Standards

Standards compliance		GB/T 18802.11 / IEC 61643-11 / NB/T 42150
Certification		CQC

#### Part number

805114