



B480-24D3



- ✦ 4-pair surge protection unit
- ✦ 24 V
- ✦ Removable protection circuit
- ✦ Wall mounting and screw connection
- ✦ UL497 A&B



 <p>Dimensions: 35mm width, 120mm height, 60mm depth. Connections: Line (top), Equipment (bottom), Earth (ground).</p>	<table border="1"> <thead> <tr> <th colspan="3">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Network</td> <td></td> <td>LS, 4-20 mA</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>24 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>28 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td></td> <td>non</td> </tr> <tr> <td>Protection mode(s)</td> <td></td> <td>Common/Differential mode</td> </tr> <tr> <td>Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)</td> <td>Up</td> <td>40 V</td> </tr> <tr> <td>Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</td> <td>Up</td> <td>20 V</td> </tr> <tr> <td>Type of diagram</td> <td></td> <td>B</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>< 4.7 Ohm</td> </tr> </tbody> </table>	Electrical Characteristics			Network		LS, 4-20 mA	Nominal line voltage	Un	24 V	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance (± 10 %)		non	Protection mode(s)		Common/Differential mode	Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up	40 V	Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up	20 V	Type of diagram		B	Line resistance		< 4.7 Ohm			
Electrical Characteristics																																											
Network		LS, 4-20 mA																																									
Nominal line voltage	Un	24 V																																									
Max. DC operating voltage	Uc	28 Vdc																																									
Max. frequency	f max.	> 3 MHz																																									
Insertion loss		< 1 dB																																									
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																									
Line inductance (± 10 %)		non																																									
Protection mode(s)		Common/Differential mode																																									
Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up	40 V																																									
Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up	20 V																																									
Type of diagram		B																																									
Line resistance		< 4.7 Ohm																																									
 <p>G: 3-electrode gas tube R: Resistor D3: 3-pole clamping diode</p>	<table border="1"> <thead> <tr> <th colspan="3">Mechanical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Technology</td> <td></td> <td>GDT+TVS diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>4 pairs</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal: cross section 0.4-1.5mm²</td> </tr> <tr> <td>Format</td> <td></td> <td>Wall mounting box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Wall mounting by screws (not supplied)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit - transmission cut-off - fault mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>S480-24D3</td> </tr> <tr> <td>Remote signaling of disconnection</td> <td></td> <td>No</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td></td> <td>0.143 kg</td> </tr> </tbody> </table>	Mechanical Characteristics			Technology		GDT+TVS diode	SPD configuration		4 pairs	Connection to Network		By screw terminal: cross section 0.4-1.5mm ²	Format		Wall mounting box	Mounting		Wall mounting by screws (not supplied)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit - transmission cut-off - fault mode 2	Spare module(s)		S480-24D3	Remote signaling of disconnection		No	Dimensions		See diagram	Weight		0.143 kg
Mechanical Characteristics																																											
Technology		GDT+TVS diode																																									
SPD configuration		4 pairs																																									
Connection to Network		By screw terminal: cross section 0.4-1.5mm ²																																									
Format		Wall mounting box																																									
Mounting		Wall mounting by screws (not supplied)																																									
Housing material		Thermoplastic UL94 V-0																																									
Operating temperature	Tu	-40/+85°C																																									
Protection rating		IP20																																									
Failsafe mode		Short-circuit - transmission cut-off - fault mode 2																																									
Spare module(s)		S480-24D3																																									
Remote signaling of disconnection		No																																									
Dimensions		See diagram																																									
Weight		0.143 kg																																									
<table border="1"> <thead> <tr> <th colspan="3">Standards</th> </tr> </thead> <tbody> <tr> <td>Standards compliance</td> <td></td> <td>IEC 61643-21 / EN 61643-21 / UL497B</td> </tr> <tr> <td>Certification</td> <td></td> <td>UL 497B</td> </tr> </tbody> </table>		Standards			Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B	Certification		UL 497B																																	
Standards																																											
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B																																									
Certification		UL 497B																																									
<table border="1"> <thead> <tr> <th colspan="3">Part number</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>72793</td> </tr> </tbody> </table>		Part number					72793																																				
Part number																																											
		72793																																									