

DLA2-48D3



- ✦ Din rail plug-in surge protector
- ✦ 2-pair
- ✦ Un: 48 V
- ✦ Shield wire protection
- ✦ Without line cut-off
- ✦ IEC 61643-21 compliance
- ✦ UL497B



	<table border="1"> <thead> <tr> <th colspan="2">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Network</td> <td>RNIS-T0, 48 V line</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un 48 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc 53 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max. > 3 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL 300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax 20 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td>non</td> </tr> <tr> <td>Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)</td> <td>Up 70 V</td> </tr> <tr> <td>Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</td> <td>Up 70 V</td> </tr> <tr> <td>Impulse current 2 x 10/350μs Test - D1 Category</td> <td>limp 5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In 5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td>4.7 Ohm</td> </tr> </tbody> </table>	Electrical Characteristics		Network	RNIS-T0, 48 V line	Nominal line voltage	Un 48 V	Max. DC operating voltage	Uc 53 Vdc	Max. frequency	f max. > 3 MHz	Max. load current @25°C	IL 300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax 20 kA	Line inductance (± 10 %)	non	Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up 70 V	Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up 70 V	Impulse current 2 x 10/350μs Test - D1 Category	limp 5 kA	Nominal discharge current C2 Category	In 5 kA	Line resistance (± 10%)	4.7 Ohm		
Electrical Characteristics																													
Network	RNIS-T0, 48 V line																												
Nominal line voltage	Un 48 V																												
Max. DC operating voltage	Uc 53 Vdc																												
Max. frequency	f max. > 3 MHz																												
Max. load current @25°C	IL 300 mA																												
Max. discharge current max. withstand @ 8/20 μs by pole	Imax 20 kA																												
Line inductance (± 10 %)	non																												
Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up 70 V																												
Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up 70 V																												
Impulse current 2 x 10/350μs Test - D1 Category	limp 5 kA																												
Nominal discharge current C2 Category	In 5 kA																												
Line resistance (± 10%)	4.7 Ohm																												
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <thead> <tr> <th colspan="2">Mechanical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Technology</td> <td>GDT+TVS diode</td> </tr> <tr> <td>SPD configuration</td> <td>2-pairs+shielded</td> </tr> <tr> <td>Connection to Network</td> <td>By screw terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td>Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating and storage temperature</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td>DLA2M-48D3</td> </tr> <tr> <td>Dimensions</td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td>0.089 kg</td> </tr> </tbody> </table>	Mechanical Characteristics		Technology	GDT+TVS diode	SPD configuration	2-pairs+shielded	Connection to Network	By screw terminal: cross section 0.5-2.5mm ²	Format	Plug-in DIN box	Mounting	Symmetrical rail 35 mm (EN 60715)	Housing material	Thermoplastic UL94 V-0	Operating and storage temperature	-40/+85°C	Protection rating	IP20	Failsafe mode	Short-circuit	Disconnection indicator	Transmission interrupt - default mode 2	Spare module(s)	DLA2M-48D3	Dimensions	See diagram	Weight	0.089 kg
Mechanical Characteristics																													
Technology	GDT+TVS diode																												
SPD configuration	2-pairs+shielded																												
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²																												
Format	Plug-in DIN box																												
Mounting	Symmetrical rail 35 mm (EN 60715)																												
Housing material	Thermoplastic UL94 V-0																												
Operating and storage temperature	-40/+85°C																												
Protection rating	IP20																												
Failsafe mode	Short-circuit																												
Disconnection indicator	Transmission interrupt - default mode 2																												
Spare module(s)	DLA2M-48D3																												
Dimensions	See diagram																												
Weight	0.089 kg																												
	<table border="1"> <thead> <tr> <th colspan="2">Standards</th> </tr> </thead> <tbody> <tr> <td>Standards compliance</td> <td>IEC 61643-21 / EN 61643-21 / UL497B</td> </tr> <tr> <td>Certification</td> <td>UL Listed</td> </tr> <tr> <td>Part number</td> <td>640312</td> </tr> </tbody> </table>	Standards		Standards compliance	IEC 61643-21 / EN 61643-21 / UL497B	Certification	UL Listed	Part number	640312																				
Standards																													
Standards compliance	IEC 61643-21 / EN 61643-21 / UL497B																												
Certification	UL Listed																												
Part number	640312																												