



MJ8-POE-A



- ✦ POE++ Compatible (IEEE 802.3bt)
- ✦ 1Gb (5-100m) with Cat6A S/FTP cabling
- ✦ Shielded RJ45 connectors
- ✦ Indoor applications, IP20 (NEMA 2)
- ✦ Metallic enclosure
- ✦ Conforms to IEC/EN 61643-21
- ✦ SPD categories D1, C3, C2, C1



P: 3-electrode GDT
DBC: Low capacitance diode

Electrical Characteristics		
Network		1Gb/s on Cat5E S/FTP cabling
Protection modes (network)		CM / DM (common mode / differential mode)
Protection modes (POE)		CM (Common Mode)
Transmission standard		IEEE 802.3bt
Lightning Protection Zones (LPZ)		0 - 3
Max. DC operating voltage	Uc	60 Vdc
Max. operating voltage (POE)	Uc	60 Vdc
Max. frequency, in the channel	f max.	100 MHz
Max. data rate		1 Gbps
Max. load current @25°C	IL	2 A
Max. POE power (4PPOE)		90 W
Max. discharge current max. withstand @ 8/20 μs, X-C (Line/Earth)	I _{max}	2 kA
Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up	80 V
Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up	700 V
Protection Level C3 (10/1000μs), 300 applications @ 10A, (Pair-Pair, POE)	Up	700 V
Impulse current D1 (10/350μs), 2 applications, 8X-C (1&2+3&6+4&5+7&8 - Earth)	I _{imp} Total	500 A
Nominal discharge current C1 (8/20μs), 300 applications X-X (Line/Line)	I _n	100V / 50A
Nominal discharge current C2 (8/20μs), 10 applications X-C (Line/Earth)	I _n	4 kV / 2 kA
Line resistance (± 10%)		~ 0 ohms
Capacitance @1MHz, X-C (Line/Earth)	C	< 5 pF
Mechanical Characteristics		
Technology		GDT+TVS diode
SPD configuration		8 wires+shielded
Connection to Network		RJ45 shielded connectors Female input/output
Cable glands		N/A
Format		Metallic box with connectors input/output
Mounting		DIN rail / Wall / Plate
Accessory(s) provided		Screw, washer, cable shoe, earthing plate, DIN rail adapter
Housing material		Metallic
Operating temperature	Tu	-40/+85°C
Ingress Protection rating		IP20 (NEMA 2)
Failsafe mode		Transmission cut-off - Fault mode 2 (short-circuit)
Disconnection indicator		Transmission interrupt - default mode 2
Pinout		(1-2)(3-6)(4-5)(7-8)
Dimensions		See diagram
Weight		0.12 kg / 0.26 lbs
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497 B IEEE 802-3af/3at/3bt
UL Category		QVGQ - Isolated Loop Circuit Protectors
UL File Number		E184939
Certification		UL 497B
Part number		
581519		