

DLU-24D3



- ✦ For DIN rail mounting
- ✦ Monobloc housing
- ✦ 1-pair
- ✦ Un: 24 V
- ✦ Transmission and protection of shield wire
- ✦ IEC 61643-21 compliance
- ✦ UL497A



	Electrical Characteristics																																										
	<table border="1"> <tr><td>Network</td><td></td><td>4-20mA, Liaison 24V</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>24 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>28 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>300 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 µs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)</td><td>Up</td><td>40 V</td></tr> <tr><td>Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)</td><td>Up</td><td>40 V</td></tr> <tr><td>Max. capacitance</td><td>C</td><td>< 50 pF</td></tr> <tr><td>Impulse current 2 x 10/350µs Test - D1 Category</td><td>limp</td><td>5 kA</td></tr> <tr><td>Nominal discharge current C2 Category</td><td>In</td><td>5 kA</td></tr> <tr><td>Line resistance (± 10%)</td><td></td><td>4.7 Ohm</td></tr> </table>		Network		4-20mA, Liaison 24V	Nominal line voltage	Un	24 V	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA	Protection mode(s)		Common/Differential mode	Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	40 V	Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	40 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350µs Test - D1 Category	limp	5 kA	Nominal discharge current C2 Category	In	5 kA	Line resistance (± 10%)	
Network		4-20mA, Liaison 24V																																									
Nominal line voltage	Un	24 V																																									
Max. DC operating voltage	Uc	28 Vdc																																									
Max. frequency	f max.	> 3 MHz																																									
Insertion loss		< 1 dB																																									
Max. load current @25°C	IL	300 mA																																									
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA																																									
Protection mode(s)		Common/Differential mode																																									
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	40 V																																									
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	40 V																																									
Max. capacitance	C	< 50 pF																																									
Impulse current 2 x 10/350µs Test - D1 Category	limp	5 kA																																									
Nominal discharge current C2 Category	In	5 kA																																									
Line resistance (± 10%)		4.7 Ohm																																									
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	Mechanical Characteristics																																										
	<table border="1"> <tr><td>Technology</td><td></td><td>GDT+TVS diode</td></tr> <tr><td>SPD configuration</td><td></td><td>1-pair+shielded</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal - cross section 1.5-2.5mm²</td></tr> <tr><td>Format</td><td></td><td>DIN box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit</td></tr> <tr><td>Disconnection indicator</td><td></td><td>Transmission interrupt - default mode 2</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> </table>		Technology		GDT+TVS diode	SPD configuration		1-pair+shielded	Connection to Network		By screw terminal - cross section 1.5-2.5mm ²	Format		DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Dimensions		See diagram								
Technology		GDT+TVS diode																																									
SPD configuration		1-pair+shielded																																									
Connection to Network		By screw terminal - cross section 1.5-2.5mm ²																																									
Format		DIN box																																									
Mounting		Symmetrical rail 35 mm (EN 60715)																																									
Housing material		Thermoplastic UL94 V-0																																									
Operating temperature	Tu	-40/+85°C																																									
Protection rating		IP20																																									
Failsafe mode		Short-circuit																																									
Disconnection indicator		Transmission interrupt - default mode 2																																									
Dimensions		See diagram																																									
Standards																																											
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497 A																																									
Certification		UL 497B																																									
Part number																																											
640503																																											