



# CITEL

## 2-pair DIN rail plug-in Data surge protector

### DLA2-24D3



- ✦ Din rail plug-in surge protector
- ✦ 2-pair
- ✦ Un: 24 V
- ✦ Shield wire protection
- ✦ Without line cut-off
- ✦ IEC 61643-21 compliance
- ✦ UL497B



	<table border="1"> <thead> <tr> <th colspan="3">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Network</td> <td></td> <td>4-20mA</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>24 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>28 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>&gt; 3 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 µs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td></td> <td>non</td> </tr> <tr> <td>Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)</td> <td>Up</td> <td>40 V</td> </tr> <tr> <td>Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)</td> <td>Up</td> <td>40 V</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In</td> <td>5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>4.7 Ohm</td> </tr> </tbody> </table>	Electrical Characteristics			Network		4-20mA	Nominal line voltage	Un	24 V	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 3 MHz	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA	Line inductance (± 10 %)		non	Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	40 V	Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	40 V	Impulse current 2 x 10/350µs Test - D1 Category	Iimp	5 kA	Nominal discharge current C2 Category	In	5 kA	Line resistance (± 10%)		4.7 Ohm			
Electrical Characteristics																																											
Network		4-20mA																																									
Nominal line voltage	Un	24 V																																									
Max. DC operating voltage	Uc	28 Vdc																																									
Max. frequency	f max.	> 3 MHz																																									
Max. load current @25°C	IL	300 mA																																									
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA																																									
Line inductance (± 10 %)		non																																									
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up	40 V																																									
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up	40 V																																									
Impulse current 2 x 10/350µs Test - D1 Category	Iimp	5 kA																																									
Nominal discharge current C2 Category	In	5 kA																																									
Line resistance (± 10%)		4.7 Ohm																																									
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <thead> <tr> <th colspan="3">Mechanical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Technology</td> <td></td> <td>GDT+TVS diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>2-pairs+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal: cross section 0.5-2.5mm<sup>2</sup></td> </tr> <tr> <td>Format</td> <td></td> <td>Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating and storage temperature</td> <td></td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>DLA2M-24D3</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td></td> <td>0.089 kg</td> </tr> </tbody> </table>	Mechanical Characteristics			Technology		GDT+TVS diode	SPD configuration		2-pairs+shielded	Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>	Format		Plug-in DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating and storage temperature		-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Spare module(s)		DLA2M-24D3	Dimensions		See diagram	Weight		0.089 kg
Mechanical Characteristics																																											
Technology		GDT+TVS diode																																									
SPD configuration		2-pairs+shielded																																									
Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>																																									
Format		Plug-in DIN box																																									
Mounting		Symmetrical rail 35 mm (EN 60715)																																									
Housing material		Thermoplastic UL94 V-0																																									
Operating and storage temperature		-40/+85°C																																									
Protection rating		IP20																																									
Failsafe mode		Short-circuit																																									
Disconnection indicator		Transmission interrupt - default mode 2																																									
Spare module(s)		DLA2M-24D3																																									
Dimensions		See diagram																																									
Weight		0.089 kg																																									
	<table border="1"> <thead> <tr> <th colspan="3">Standards</th> </tr> </thead> <tbody> <tr> <td>Standards compliance</td> <td></td> <td>IEC 61643-21 / EN 61643-21 / UL497B</td> </tr> <tr> <td>Certification</td> <td></td> <td>UL Listed</td> </tr> <tr> <th colspan="3">Part number</th> </tr> <tr> <td></td> <td></td> <td>640311</td> </tr> </tbody> </table>	Standards			Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B	Certification		UL Listed	Part number					640311																											
Standards																																											
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B																																									
Certification		UL Listed																																									
Part number																																											
		640311																																									

