



UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Cat No(s): DAC50-20-320

SPD Type	Volts (V)	AC/DC DC PV	Phase	Amps (A)	Ambient Min(°C)	Ambient Max(°C)	Mode	VPR (Vpk)	MLV (Vpk)	MCOV (V)	Vn (Vdc)	In (kA)	SCCR (kA)	Notes
4CA	400/230	AC	3Y	n/a	-40	85	L-L	-	3340	640	n/a	20	n/a	1
							L-G	-	2370	320	n/a			
4CA	400/230	AC	3Y	n/a	-40	85	L-N	-	3340	640	n/a	20	n/a	1
							L-G	-	2370	320	n/a			
							N-G	-	2370	320	n/a			

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08

Note 1 - Suitable for Factory wiring only.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2020-12-02

Last Revised: 2021-09-30

© 2022 UL LLC

