



UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Cat No(s): DS252VG-120

<u>SPD Type</u>	<u>Volts (V)</u>	<u>AC/DC DC PV</u>	<u>Phase</u>	<u>Amps (A)</u>	<u>Ambient Min(°C)</u>	<u>Ambient Max(°C)</u>	<u>Mode</u>	<u>VPR (Vpk)</u>	<u>MLV (Vpk)</u>	<u>MCOV (V)</u>	<u>Vn (Vdc)</u>	<u>In (kA)</u>	<u>SCCR (kA)</u>	<u>Notes</u>
4CA	240/120	AC	1S	n/a	-40	85	L-L	-	3160	300	n/a	20	n/a	1
							L-G	-	1580	150	n/a			
4CA	240/120	AC	1S	n/a	-40	85	L-N	-	3160	300	n/a	20	n/a	1
							L-G	-	1580	150	n/a			

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08

Note 1 - Suitable for Factory wiring only.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2010-02-26

Last Revised: 2021-09-30

© 2022 UL Solutions

