





CITEL



Type 2 AC surge protector - 3-phase

DS43-320

- » Discover our latest innovation : the [DAC50-30-320](#)
- » Type 2 AC Multipolar surge protector
- » In : 20 kA
- » I_{max} total : 120 kA
- » Pluggable module for each phase
- » Remote signaling option
- » EN 61643-11, IEC 61643-11 compliance
- » UL1449 ed.5



Electrical Characteristics		
SPD type	IEC	2
Network		230/400V
AC system		TNC
Nominal line voltage	Un	230 Vac
Max. AC operating voltage	Uc	320 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. <i>Without disconnection</i>	UT	335 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn <i>Without disconnection or with safety disconnection</i>	UT	440 Vac disconnection
Residual Current <i>Leakage current to Ground</i>	I _{pe}	< 1 mA
Follow current	I _f	None
Nominal discharge current <i>15 x 8/20 μs impulses</i>	I _n	20 kA
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max}	40 kA
Total Maximum discharge current <i>max. total withstand @ 8/20 μs</i>	I _{max} Total	120 kA
Connection mode(s)		L/PE
Protection mode(s)		Common mode
Protection level L/PE <i>@ I_n (8/20μs)</i>	Up L/PE	1.5 kV
Admissible short-circuit current	I _{scrr}	25 000 A
Mechanical Characteristics		
Technology		MOV
SPD configuration		3-phase
Connection to Network		By screw terminals: 2.5-25mm ² / by bus
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator by pole
Spare module(s)		DSM40-320
Remote signaling of disconnection		option DS43S-320 : output on changeover contact
Dimensions		See diagram
Weight		0.276 kg
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		Fuses type gG - 50 A
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification		cRUus
Part number		
461903		

