

Type 2 AC surge protector - 3-phase+N

DAC50-40-530



- Type 2 AC multipolar surge protector
- In: 20 kA
- Imax: 50 kA
- Pluggable module for each phase
- Remote signaling option
- EN 61643-11, IEC 61643-11 certified





V: High-energy varistor
Ft: Thermal fuse
t°: Thermal disconnection system
MI: Disconnection indicator

Electrical Characteristics		
SPD type	IEC	2
Network		277/480 V 3-phase
AC system		TNS
Max. AC operating voltage	Uc	530 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. *Without disconnection*	UT	700 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn *Without disconnection or with safety disconnection*	UT	920 Vac disconnection
Residual Current *Leakage current to Ground*	Ipe	< 1 mA
Follow current	If	None
Nominal discharge current *15 x 8/20 µs impulses*	In	20 kA
Max. discharge current *max. withstand @ 8/20 µs by pole*	Imax	50 kA
Total Maximum discharge current *max. total withstand @ 8/20 µs*	Imax Total	200 kA
Protection mode(s)		L/PE and N/PE
Protection level N/PE *@ In (8/20µs)*	Up N/PE	2.4 kV
Protection level L/PE *@ In (8/20µs)*	Up L/PE	2.4 kV
Protection level N/PE at 5 kA *@ 5 kA (8/20µs)*	Up-5kA	2 kV
Residual voltage L/PE at 5 kA *@ 5 kA (8/20µs)*	Up-5kA	2 kV
Admissible short-circuit current	Isccr	50 000 A
UL Electrical Characteristics		
UL Category		UL Recognized Type 4CA
Maximum Continuous Operating Voltage*(L-L/L-N)*	MCOV	1060 V
Maximum Continuous Operating Voltage*(L-G/N-G)*	MCOV	530 V
Maximum Limiting Voltage*(L-L/L-N)*	MLV	5170 V
Maximum Limiting Voltage*(L-G/N-G)*	MLV	3120 V
Nominal discharge current	In	20 kA
Mechanical Characteristics		
Technology		MOV
SPD configuration		3-phase+Neutral
Connection to Network		By screw terminals: 2.5-25mm² (35mm² rigid)
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Ingress Protection rating		IP20 (NEMA 2)
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator by pole - Red/Green
Spare module(s)		MDAC50-530
Remote signaling of disconnection		option DAC50S-40-530 : output on changeover contact
Dimensions		See diagram - 4TE (EN43880)
Weight		0.446 kg
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		50 A min. - 125 A max. - Fuses Type gG
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11
Certification		OVE
Part number		
821110514		