

Type 2+3 PV surge protector - CTC Technology

DPVN40C-21Y-1200



- Type 2+3 surge protector for Photovoltaic
- CTC Technology
- Discharge currents Imax/Itotal: 40/60 kA (8/20µs)
- Common/Differential mode protection
- IEC 61643-31, EN 61643-31, EN 50539-11, UL1449 ed.5 compliance
- Certified EN 61643-31 and IEC 61643-31





V: High-energy varistor
Ft: Thermal fuse
t°: Thermal disconnection system
MI: Mechanical status indicator

Electrical Characteristics		
SPD type	IEC	2
Network		PV 1000 Vdc
Nominal PV voltage	Uocstc	1000 Vdc
Max. PV operating voltage	Ucpv	1200 Vdc
Residual Current *Leakage current to Ground*	Ipe	< 0.2 mA
PV Permanent Operating current *Current consumption at Ucpv*	Icpv	< 0.1 mA
Follow current	If	None
Nominal discharge current *15 x 8/20 µs impulses*	In	20 kA
Max. discharge current *max. withstand @ 8/20 µs by pole*	Imax	40 kA
Total Maximum discharge current *max. total withstand @ 8/20 µs*	Imax Total	60 kA
Withstand on Combination waveform IEC 61643-11 *Class III test: 1.2/50µs - 8/20µs*	Uoc	6 kV
Current withstand short circuit PV	Iscpv	15 000 A
Connection mode(s)		+/-/PE
Protection mode(s)		Differential/Common mode
Protection level +/- *@ In (8/20µs)*	Up	4.3 kV
Protection level +/PE (-/PE) *@ In (8/20µs)*	Up	4,1 kV
Protection level at 5 kA *@ 5 kA (8/20µs)*	Up	3,5 kV
Protection level at Uoc *@ Uoc (1.2/50 µs)*	Up	3,1 kV
Mechanical Characteristics		
Technology		MOV
Connection to Network		By screw terminals: 2.5-25mm² (35mm²) / by bus
Format		Compact monobloc box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		All pole disconnection from PV network
Disconnection indicator		1 mechanical indicator - Red/Green
Remote signaling of disconnection		Option DPVN40CS-21Y-1200 - output on changeover contact
Dimensions		See diagram - 2.5TE (EN43880)
Weight		0.285 kg
Disconnectors		
Thermal disconnector		CTC Technology integrated
Back-up protection device		Without
Standards		
Standards compliance		IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5
Certification		KEMA
Part number		
65111102		