

*Type 2 (or 3) AC surge protector - 3-phase+N*

# DS14-120




- **Discover our latest innovation : the DAC15C-40-150**
- Type 2 (or 3) AC Multipolar surge protector
- In : 5 kA
- Imax total: 40 kA
- Pluggable module by phase
- Remote signaling option
- EN 61643-11, IEC 61643-11, UL1449 ed.5 compliance




**V: High-energy varistor**
**Ft: Thermal fuse**
**t°: Thermal disconnection system**
**MI: Disconnection indicator**

| | | |
|---|---|---|
| **Electrical Characteristics** | | |
| SPD type | IEC | 2+3 |
| Network | | 120/208 V |
| AC system | | TNS |
| Nominal line voltage | Un | 120 Vac |
| Max. AC operating voltage | Uc | 150 Vac |
| Temporary Over Voltage (TOV) Characteristics - 5 sec.<br>*Without disconnection* | UT | 180 Vac withstand |
| Temporary Over Voltage (TOV) Characteristics - 120 mn<br>*Without disconnection or with safety disconnection* | UT | 230 Vac disconnection |
| Residual Current<br>*Leakage current to Ground* | Ipe | < 2 mA |
| Follow current | If | None |
| Nominal discharge current<br>*15 x 8/20 µs impulses* | In | 5 kA |
| Max. discharge current<br>*max. withstand @ 8/20 µs by pole* | Imax | 10 kA |
| Total Maximum discharge current<br>*max. total withstand @ 8/20 µs* | Imax Total | 40 kA |
| Withstand on Combination waveform IEC 61643-11<br>*Class III test: 1.2/50µs - 8/20µs* | Uoc | 10 kV |
| Withstand on overvoltages IEEE C62.41.1 | | 10 kV |
| Connection mode(s) | | L/PE and N/PE |
| Protection mode(s) | | Common mode |
| Protection level L/PE<br>*@ In (8/20µs)* | Up L/PE | 0.6 kV |
| Admissible short-circuit current | Isccr | 25 000 A |
| **Mechanical Characteristics** | | |
| Technology | | MOV |
| SPD configuration | | 3-phase+Neutral |
| Connection to Network | | By screw terminals: 2.5-25mm² / by bus |
| Format | | Plug-in modular box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection from AC network |
| Disconnection indicator | | 1 mechanical indicator by pole |
| Spare module(s) | | DSM10-120 |
| Remote signaling of disconnection | | option DS14S-120 : output on changeover contact |
| Dimensions | | See diagram |
| Weight | | 0.34 kg |
| **Disconnectors** | | |
| Thermal disconnector | | Internal |
| Installation ground fault breaker | | Type 'S' or delayed |
| Back-up protection device | | 20 A min. - 125 A max. - Fuses type gG |
| **Standards** | | |
| Standards compliance | | IEC 61643-11 / EN 61643-11 / UL1449 ed.5 |
| Certification | | UL Recognized |
| **Part number** | | |
| **471602** | | |