


*Type 2 PV surge protector*

# DS50PV-600/51




- Type 2 surge protector for Photovoltaic
- PV voltage: 600 Vdc
- In: 15 kA
- Imax: 40 kA
- Pluggable module
- Remote signaling (option)
- UTE C61-740-51, EN 50539-11 compliance




**V: High-energy varistor**
**Ft: Thermal fuse**
**t°: Thermal disconnection system**
**MI: Disconnection indicator**

| **Electrical Characteristics** | | |
|---|---|---|
| SPD type | IEC | 2 |
| Network | | PV 500 Vdc |
| Nominal PV voltage | Uocstc | 600 Vdc |
| Max. PV operating voltage | Ucpv | 720 Vdc |
| Residual Current<br>*Leakage current to Ground* | Ipe | < 0.2 mA |
| PV Permanent Operating current<br>*Current consumption at Ucpv* | Icpv | < 0.1 mA |
| Follow current | If | None |
| Nominal discharge current<br>*15 x 8/20 µs impulses* | In | 15 kA |
| Max. discharge current<br>*max. withstand @ 8/20 µs by pole* | Imax | 40 kA |
| Total Maximum discharge current<br>*max. total withstand @ 8/20 µs* | Imax Total | 60 kA |
| Current withstand short circuit PV | Iscpv | 15 000 A |
| Connection mode(s) | | +/-/PE |
| Protection mode(s) | | Common mode |
| Protection level +/PE (-/PE)<br>*@ In (8/20µs)* | Up | 2.8 kV |
| **Mechanical Characteristics** | | |
| Technology | | MOV |
| Connection to Network | | By screw terminals: 2.5-25mm² |
| Format | | Plug-in modular box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection SPD of the PV line |
| Disconnection indicator | | 2 mechanical indicators - Red/Green |
| Spare module(s) | | DSM50PV-600/51 |
| Remote signaling of disconnection | | Option DS50PVS-600/51 - output on changeover contact |
| Dimensions | | See diagram |
| Weight | | 0.249 kg |
| **Disconnectors** | | |
| Thermal disconnector | | Internal |
| Back-up protection device | | Without |
| **Standards** | | |
| Standards compliance | | EN 61643-31 / EN 50539-11 |
| Certification | | |
| **Part number** | | |
| **480421** | | |