




- Security camera surge protector
- AC + Cat.5 (connector RJ45)
- Compact aluminium housing
- Rail DIN mounting or plate



Electrical Characteristics		
SPD type		2+3
Network		12 Vac/Vdc
Nominal line voltage	Un	12 Vac/Vdc
Max. DC operating voltage	Uc	15 Vac/Vdc
Insertion loss		< 1 dB
Max. load current @25°C	IL	5 A
Nominal discharge current <i>15 x 8/20 μs impulses</i>	In	5 kA
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	Imax	10 kA
Withstand on Combination waveform IEC 61643-11 <i>Class III test: 1.2/50μs - 8/20μs</i>	Uoc	10 kV / 5 kA
Protection mode(s)		Common/Differential mode
Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i>	Up	220 V
Protection level L/N <i>@ In (8/20μs)</i>	Up L/N	20 V
Protection level L/PE <i>@ In (8/20μs)</i>	Up L/PE	20 V
Nominal discharge current <i>C2 Category</i>	In	2.5 kA
ELEC		
Protection level @ In (8/20μs)	Up	20 V
ELEC		
Network		4 pairs Ethernet 100 Base-TX
ELEC		
Max. DC operating voltage	Uc	8 Vdc
ELEC		
Max. frequency	f max.	125 MHz
ELEC		
Insertion loss		< 1dB
ELEC		
Max. load current@25°C	IL	300 mA
ELEC		
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	Imax	5 kA
ELEC		
Protection level @ In (8/20μs)	Up	20 V
ELEC		
Protection level L/N @ In (8/20μs)	Up L/N	20 V
ELEC		
Protection level L/PE @ In (8/20μs)	Up L/PE	20 V
ELEC		
Nominal discharge current <i>C2 Category</i>	In	2.5 kA
Mechanical Characteristics		
Technology		MOV+GDT
Connection to Network		By screw terminals: 2.5mm ² max.
Format		DIN rail or flange
Mounting		DIN rail or plate (flange)
Housing material		Anodized aluminum
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection and Power cut off
Disconnection indicator		Green LED OFF and line cut off
Voltage/operating indicator		Green Led ON
Dimensions		See diagram
Disconnectors		
Thermal disconnecter		Internal
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5

Part number

420413