





Type 2 AC surge protector - Single-phase

CITEL

DS72R-400/G



- › Discover our latest innovation : the [DAC80-11-440](#) -Re-inforced Type 2 AC surge protector
- › I_n : 30 kA
- › I_{max} : 70 kA
- › Pluggable module by phase
- › Remote signaling option
- › IEC 61643-11, EN 61643-11 and UL1449 ed.5 compliance



V: High-energy varistor
 GSG: Specific Gas Tube
 Ft: Thermal fuse
 t*: Thermal disconnection system
 MI: Disconnection indicator

Electrical Characteristics		
SPD type	IEC	2
Network		230/400 V
AC system		TT
Nominal line voltage	U_n	230 Vac
Max. AC operating voltage	U_c	255 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. <i>Without disconnection</i>	UT	335 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn <i>Without disconnection or with safety disconnection</i>	UT	440 Vac disconnection
Temporary Over Voltage N/PE (TOV HT) <i>Without disconnection or with safety disconnection</i>	UT	1200 V/300A/200 ms withstand
Residual Current <i>Leakage current to Ground</i>	I_{pe}	None
Follow current	I_f	None
Nominal discharge current <i>15 x 8/20 μs impulses</i>	I_n	30 kA
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I_{max}	70 kA
Total Maximum discharge current <i>max. total withstand @ 8/20 μs</i>	I_{max} Total	70 kA
Connection mode(s)		L/N and N/PE
Protection mode(s)		Common/Differential mode
Residual voltage at 5 kA <i>@ 5 kA (8/20μs)</i>	U_{p-5kA}	0.9 kV
Protection level L/N <i>@ In (8/20μs)</i>	$U_{p L/N}$	1.4 kV
Protection level N/PE <i>@ In (8/20μs)</i>	$U_{p N/PE}$	1.5 kV
Admissible short-circuit current	I_{scrr}	25 000 A
Mechanical Characteristics		
Technology		MOV
SPD configuration		Single phase
Connection to Network		By screw terminals: 2.5-25mm ² / by bus
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	T_u	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		2 mechanical indicators by pole
Spare module(s)		DSM70R-230 + DSM70G-600
Remote signaling of disconnection		option DS72RS-230/G : output on changeover contact
Dimensions		See diagram
Weight		0.246 kg
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		100 A min. - 125 A max. - Fuses type gG
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification		UL Recognized
Part number		
491411		

