



CITEL

2-pair DIN rail plug-in Data surge protector

DLA2-24DBC



- ▷ Din rail plug-in surge protector
- ▷ 2-pair
- ▷ Un: 48 V
- ▷ Shield wire protection
- ▷ Without line cut-off
- ▷ IEC 61643-21 compliance



	Electrical Characteristics																																								
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td colspan="2">Fipway, WorldFIP, FieldBus-h2</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>24 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>28 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 20 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>I_{max}</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td></td> <td>non</td> </tr> <tr> <td>Protection level @ In (8/20 μs)</td> <td>Up L/L</td> <td>75 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>< 50 pF</td> </tr> <tr> <td>Impulse current 2 x 10/350 μs Test - D1 Category</td> <td>I_{imp}</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>I_n</td> <td>5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>4.7 Ohm</td> </tr> </table>		Network	Fipway, WorldFIP, FieldBus-h2		Nominal line voltage	Un	24 V	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 20 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA	Line inductance (± 10 %)		non	Protection level @ In (8/20 μs)	Up L/L	75 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA	Nominal discharge current C2 Category	I _n	5 kA	Line resistance (± 10%)		4.7 Ohm
Network	Fipway, WorldFIP, FieldBus-h2																																								
Nominal line voltage	Un	24 V																																							
Max. DC operating voltage	Uc	28 Vdc																																							
Max. frequency	f max.	> 20 MHz																																							
Insertion loss		< 1 dB																																							
Max. load current @25°C	IL	300 mA																																							
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA																																							
Line inductance (± 10 %)		non																																							
Protection level @ In (8/20 μs)	Up L/L	75 V																																							
Max. capacitance	C	< 50 pF																																							
Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA																																							
Nominal discharge current C2 Category	I _n	5 kA																																							
Line resistance (± 10%)		4.7 Ohm																																							
Mechanical Characteristics																																									
<table border="1"> <tr> <td>Technology</td> <td colspan="2">GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td colspan="2">2-pairs+shielded</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">By screw terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td colspan="2">Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td colspan="2">Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td colspan="2">Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating and storage temperature</td> <td colspan="2">-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td colspan="2">IP20</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td colspan="2">Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td colspan="2">DLA2M-48dBC</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">See diagram</td> </tr> </table>			Technology	GDT+Clamping diode		SPD configuration	2-pairs+shielded		Connection to Network	By screw terminal: cross section 0.5-2.5mm ²		Format	Plug-in DIN box		Mounting	Symmetrical rail 35 mm (EN 60715)		Housing material	Thermoplastic UL94 V-0		Operating and storage temperature	-40/+85°C		Protection rating	IP20		Failsafe mode	Short-circuit		Disconnection indicator	Transmission interrupt - default mode 2		Spare module(s)	DLA2M-48dBC		Dimensions	See diagram				
Technology	GDT+Clamping diode																																								
SPD configuration	2-pairs+shielded																																								
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²																																								
Format	Plug-in DIN box																																								
Mounting	Symmetrical rail 35 mm (EN 60715)																																								
Housing material	Thermoplastic UL94 V-0																																								
Operating and storage temperature	-40/+85°C																																								
Protection rating	IP20																																								
Failsafe mode	Short-circuit																																								
Disconnection indicator	Transmission interrupt - default mode 2																																								
Spare module(s)	DLA2M-48dBC																																								
Dimensions	See diagram																																								
Standards																																									
Standards compliance	IEC 61643-21 / EN 61643-21																																								
Part number																																									
640331																																									

