



# CITEL

## 2-pair DIN rail plug-in Data surge protector

### DLA2-24DBC



- ↳ Din rail plug-in surge protector
- ↳ 2-pair
- ↳ Un: 48 V
- ↳ Shield wire protection
- ↳ Without line cut-off
- ↳ IEC 61643-21 compliance



	<b>Electrical Characteristics</b>																																					
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td colspan="2">Fipway, WorldFIP, FieldBus-h2</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>24 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>28 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>&gt; 20 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>&lt; 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>I<sub>max</sub></td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection level Following the test category C3 (IEC61643-21) - Line/Line</td> <td>Up</td> <td>75 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>&lt; 50 pF</td> </tr> <tr> <td>Impulse current 2 x 10/350 μs Test - D1 Category</td> <td>I<sub>imp</sub></td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>I<sub>n</sub></td> <td>5 kA</td> </tr> </table>		Network	Fipway, WorldFIP, FieldBus-h2		Nominal line voltage	Un	24 V	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 20 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	20 kA	Line inductance		No	Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	75 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350 μs Test - D1 Category	I <sub>imp</sub>	5 kA	Nominal discharge current C2 Category	I <sub>n</sub>	5 kA
Network	Fipway, WorldFIP, FieldBus-h2																																					
Nominal line voltage	Un	24 V																																				
Max. DC operating voltage	Uc	28 Vdc																																				
Max. frequency	f max.	> 20 MHz																																				
Insertion loss		< 1 dB																																				
Max. load current @25°C	IL	300 mA																																				
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	20 kA																																				
Line inductance		No																																				
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	75 V																																				
Max. capacitance	C	< 50 pF																																				
Impulse current 2 x 10/350 μs Test - D1 Category	I <sub>imp</sub>	5 kA																																				
Nominal discharge current C2 Category	I <sub>n</sub>	5 kA																																				
<b>Mechanical Characteristics</b>																																						
<table border="1"> <tr> <td>Technology</td> <td>GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td>2-pairs+shielded</td> </tr> <tr> <td>Connection to Network</td> <td>By screw terminal: cross section 0.5-2.5mm<sup>2</sup></td> </tr> <tr> <td>Format</td> <td>Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating and storage temperature</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td>DLA2M-48DBC</td> </tr> <tr> <td>Dimensions</td> <td>See diagram</td> </tr> </table>		Technology	GDT+Clamping diode	SPD configuration	2-pairs+shielded	Connection to Network	By screw terminal: cross section 0.5-2.5mm <sup>2</sup>	Format	Plug-in DIN box	Mounting	Symmetrical rail 35 mm (EN 60715)	Housing material	Thermoplastic UL94 V-0	Operating and storage temperature	-40/+85°C	Protection rating	IP20	Failsafe mode	Short-circuit	Disconnection indicator	Transmission interrupt - default mode 2	Spare module(s)	DLA2M-48DBC	Dimensions	See diagram													
Technology	GDT+Clamping diode																																					
SPD configuration	2-pairs+shielded																																					
Connection to Network	By screw terminal: cross section 0.5-2.5mm <sup>2</sup>																																					
Format	Plug-in DIN box																																					
Mounting	Symmetrical rail 35 mm (EN 60715)																																					
Housing material	Thermoplastic UL94 V-0																																					
Operating and storage temperature	-40/+85°C																																					
Protection rating	IP20																																					
Failsafe mode	Short-circuit																																					
Disconnection indicator	Transmission interrupt - default mode 2																																					
Spare module(s)	DLA2M-48DBC																																					
Dimensions	See diagram																																					
<b>Standards</b>																																						
Standards compliance		IEC 61643-21 / EN 61643-21																																				
<b>Part number</b>																																						
640331																																						

