



2-pair monobloc Data surge protector

CITEL

DLU2-06D3



- For DIN rail mounting
- Monobloc housing
- 2-pair
- Un: 6 V
- IEC 61643-21 compliance
- UL497A certified



| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|--|----------------------|--|-------------------------------------|----------------------|----|---------|---------------------------|----|--|----------------|--------|---------|----------------|--|-----------------------------------|-------------------------|----|------------------------|---|------|-----------|-------------------------|--|------|--------------------|--|--------------------------|---------------------------------|--------|---|-----------------------------------|---|---------|--|------|-------------|---------------------------------------|----|----------|-------------------------|--|---------|
| | Electrical Characteristics | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p> | <table border="1"> <tr><td>Network</td><td></td><td>RS422, RS485</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>6 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>10 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>300 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Line inductance (± 10%)</td><td></td><td>non</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level @ In (8/20 μs)</td><td>Up L/L</td><td>20 V</td></tr> <tr><td>Max. capacitance</td><td>C</td><td>< 50 pF</td></tr> <tr><td>Impulse current 2 x 10/350 μs Test - D1 Category</td><td>Iimp</td><td>5 kA</td></tr> <tr><td>Nominal discharge current C2 Category</td><td>In</td><td>5 kA</td></tr> <tr><td>Line resistance (± 10%)</td><td></td><td>4.7 Ohm</td></tr> </table> | | Network | | RS422, RS485 | Nominal line voltage | Un | 6 V | Max. DC operating voltage | Uc | 10 Vdc | Max. frequency | f max. | > 3 MHz | Insertion loss | | < 1 dB | Max. load current @25°C | IL | 300 mA | Max. discharge current max. withstand @ 8/20 μs by pole | Imax | 20 kA | Line inductance (± 10%) | | non | Protection mode(s) | | Common/Differential mode | Protection level @ In (8/20 μs) | Up L/L | 20 V | Max. capacitance | C | < 50 pF | Impulse current 2 x 10/350 μs Test - D1 Category | Iimp | 5 kA | Nominal discharge current C2 Category | In | 5 kA | Line resistance (± 10%) | | 4.7 Ohm |
| Network | | RS422, RS485 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Nominal line voltage | Un | 6 V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max. DC operating voltage | Uc | 10 Vdc | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max. frequency | f max. | > 3 MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insertion loss | | < 1 dB | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max. load current @25°C | IL | 300 mA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max. discharge current max. withstand @ 8/20 μs by pole | Imax | 20 kA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Line inductance (± 10%) | | non | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Protection mode(s) | | Common/Differential mode | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Protection level @ In (8/20 μs) | Up L/L | 20 V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max. capacitance | C | < 50 pF | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Impulse current 2 x 10/350 μs Test - D1 Category | Iimp | 5 kA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Nominal discharge current C2 Category | In | 5 kA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Line resistance (± 10%) | | 4.7 Ohm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Mechanical Characteristics | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | <table border="1"> <tr><td>Technology</td><td></td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td></td><td>2 pairs</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal - cross section 1.5-2.5mm²</td></tr> <tr><td>Format</td><td></td><td>DIN box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit</td></tr> <tr><td>Disconnection indicator</td><td></td><td>Transmission interrupt - default mode 2</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>No</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.063 kg</td></tr> </table> | | Technology | | GDT+Clamping diode | SPD configuration | | 2 pairs | Connection to Network | | By screw terminal - cross section 1.5-2.5mm ² | Format | | DIN box | Mounting | | Symmetrical rail 35 mm (EN 60715) | Housing material | | Thermoplastic UL94 V-0 | Operating temperature | Tu | -40/+85°C | Protection rating | | IP20 | Failsafe mode | | Short-circuit | Disconnection indicator | | Transmission interrupt - default mode 2 | Remote signaling of disconnection | | No | Dimensions | | See diagram | Weight | | 0.063 kg | | | |
| Technology | | GDT+Clamping diode | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SPD configuration | | 2 pairs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Connection to Network | | By screw terminal - cross section 1.5-2.5mm ² | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Format | | DIN box | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Mounting | | Symmetrical rail 35 mm (EN 60715) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Housing material | | Thermoplastic UL94 V-0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating temperature | Tu | -40/+85°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Protection rating | | IP20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Failsafe mode | | Short-circuit | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Disconnection indicator | | Transmission interrupt - default mode 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remote signaling of disconnection | | No | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Dimensions | | See diagram | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Weight | | 0.063 kg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Standards | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | <table border="1"> <tr><td>Standards compliance</td><td></td><td>IEC 61643-21 / EN 61643-21 / UL497A</td></tr> <tr><td>Certification</td><td></td><td>UL 497B</td></tr> </table> | | Standards compliance | | IEC 61643-21 / EN 61643-21 / UL497A | Certification | | UL 497B | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Standards compliance | | IEC 61643-21 / EN 61643-21 / UL497A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Certification | | UL 497B | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Part number | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 640402 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

