



1-pair Data surge protector unit

CITEL

B180-48D3



- ↳ Compact 1-pair surge protection unit
- ↳ 48 V
- ↳ Removable protection circuit
- ↳ Wall mounting and screw connection
- ↳ UL497 A&B



	Electrical Characteristics																																																																
<p>G: 3-electrode gas tube R: Resistor D3: 3-pole clamping diode</p>	Mechanical Characteristics																																																																
<table border="1"> <tr><td>Network</td><td></td><td>48 V line</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>48 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>53 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level @ In (8/20 μs)</td><td>Up L/L</td><td>70 V</td></tr> <tr><td>Protection level @ In (8/20 μs)</td><td>Up L/PE</td><td>20 V</td></tr> <tr><td>Line resistance</td><td></td><td>< 4.7 Ohm</td></tr> </table>	Network		48 V line	Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Protection mode(s)		Common/Differential mode	Protection level @ In (8/20 μs)	Up L/L	70 V	Protection level @ In (8/20 μs)	Up L/PE	20 V	Line resistance		< 4.7 Ohm	<table border="1"> <tr><td>Technology</td><td></td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td></td><td>1 pair</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal: cross section 0.4-1.5mm²</td></tr> <tr><td>Format</td><td></td><td>Wall mounting box</td></tr> <tr><td>Mounting</td><td></td><td>Wall mounting by screws (not supplied)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit - transmission cut-off - fault mode 2</td></tr> <tr><td>Spare module(s)</td><td></td><td>S180-48D3</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> </table>		Technology		GDT+Clamping diode	SPD configuration		1 pair	Connection to Network		By screw terminal: cross section 0.4-1.5mm ²	Format		Wall mounting box	Mounting		Wall mounting by screws (not supplied)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit - transmission cut-off - fault mode 2	Spare module(s)		S180-48D3	Dimensions		See diagram
Network		48 V line																																																															
Nominal line voltage	Un	48 V																																																															
Max. DC operating voltage	Uc	53 Vdc																																																															
Max. frequency	f max.	> 3 MHz																																																															
Insertion loss		< 1 dB																																																															
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																																															
Protection mode(s)		Common/Differential mode																																																															
Protection level @ In (8/20 μs)	Up L/L	70 V																																																															
Protection level @ In (8/20 μs)	Up L/PE	20 V																																																															
Line resistance		< 4.7 Ohm																																																															
Technology		GDT+Clamping diode																																																															
SPD configuration		1 pair																																																															
Connection to Network		By screw terminal: cross section 0.4-1.5mm ²																																																															
Format		Wall mounting box																																																															
Mounting		Wall mounting by screws (not supplied)																																																															
Housing material		Thermoplastic UL94 V-0																																																															
Operating temperature	Tu	-40/+85°C																																																															
Protection rating		IP20																																																															
Failsafe mode		Short-circuit - transmission cut-off - fault mode 2																																																															
Spare module(s)		S180-48D3																																																															
Dimensions		See diagram																																																															
Standards																																																																	
Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																																																																
Certification	UL 497B																																																																
Part number																																																																	
510402																																																																	

