



CITEL

'Quarter wave' coaxial protector

PRC2100-NW/FF



- ↳ 'Quarter wave' coaxial protector type N
- ↳ Frequency : 1800-2400 MHz
- ↳ Low insertion loss
- ↳ I_{max} > 50 kA
- ↳ Maintenance free
- ↳ Bi-directional
- ↳ IP65



Electrical Characteristics		
Max. frequency	f max.	1800-2400MHz
Frequency range	f	1800-2400 MHz
Insertion loss		< 0.2 dB
Return loss		> 20 dB
Impedance		50 ohms
VSWR		<1.2:1
Max. load current @25°C	IL	10 A
Max. discharge current <i>max. withstand @ 8/20 µs by pole</i>	I _{max}	50 kA
Protection mode(s)		Common mode
Protection level @ I _n (8/20µs)	Up	< 30 V
Impulse current <i>2 x 10/350µs Test - D1 Category</i>	I _{imp}	25 kA
Nominal discharge current <i>C2 Category</i>	I _n	25 kA
Max Power @f max.		830 W
Max Power @f mini.		958 W
PIM 3rd order (2x20W)		< -160 dBc
DC Pass		No
Mechanical Characteristics		
Technology		Quarter Wave
Connection to Network		Connector N Female/Female
Mounting		Feedthrough
Housing material		Brass/Surface plating: Cu Zn Sn
Operating temperature	T _u	-40/+85°C
Protection rating		IP65
Failsafe mode		Without
Dimensions		See diagram
Contacts		Bronze/Surface Au-Ag
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497E
RohS compliance		Yes
Part number		
621172		

