



Surge protector for LED lighting system Class 1

CITEL

DSLSP1-120L/Y



- Type 2 (or 3) surge protectors for LED
- Very compact (low profile)
- DIN rail mounting
- Screw terminal connection
- Status indicator
- Disconnection AC end of life
- EN 61643-11, IEC 61643-11 compliance



	<table border="1"> <thead> <tr> <th colspan="2">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>SPD type</td> <td>2 (or 3)</td> </tr> <tr> <td>Network</td> <td>120 V single-phase or 2-phase</td> </tr> <tr> <td>AC system</td> <td>TN</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un 120 Vac</td> </tr> <tr> <td>Max. AC operating voltage</td> <td>Uc 150 Vac</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL 10 A</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td> <td>UT 120 Vac withstand</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td> <td>UT 230 Vac disconnection</td> </tr> <tr> <td>Residual Current Leakage current to Ground</td> <td>Ipe None</td> </tr> <tr> <td>Nominal discharge current 15 x 8/20 μs impulses</td> <td>In 5 kA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax 10 kA</td> </tr> <tr> <td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td> <td>Uoc 10 kV / 5 kA</td> </tr> <tr> <td>Withstand on overvoltages IEEE C62.41.1</td> <td>10 kV / 10 kA</td> </tr> <tr> <td>Protection mode(s)</td> <td>Common/Differential mode</td> </tr> <tr> <td>Protection level L/N @ In (8/20μs)</td> <td>Up L/N 1.5 kV</td> </tr> <tr> <td>Protection level L/PE @ In (8/20μs)</td> <td>Up L/PE 1.5 kV</td> </tr> <tr> <td>Admissible short-circuit current</td> <td>Iscrc 10 000 A</td> </tr> <tr> <th colspan="2">Mechanical Characteristics</th> </tr> <tr> <td>Technology</td> <td>MOV+GDT</td> </tr> <tr> <td>Connection to Network</td> <td>Screw terminal 2.5 mm² max. Earthing conductor 2 mm² - length 60 cm</td> </tr> <tr> <td>Mounting</td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu -40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td>Disconnection from AC network</td> </tr> <tr> <td>Disconnection indicator</td> <td>LED green OFF and AC network cut-off</td> </tr> <tr> <td>Voltage/operating indicator</td> <td>Green Led ON</td> </tr> <tr> <td>Dimensions</td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td>0.062 kg</td> </tr> <tr> <th colspan="2">Disconnectors</th> </tr> <tr> <td>Thermal disconnector</td> <td>Internal</td> </tr> <tr> <td>Installation ground fault breaker</td> <td>Type 'S' or delayed</td> </tr> <tr> <th colspan="2">Standards</th> </tr> <tr> <td>Standards compliance</td> <td>EN 61643-11 / IEC 61643-11</td> </tr> <tr> <td>Part number</td> <td>352922</td> </tr> </tbody> </table>	Electrical Characteristics		SPD type	2 (or 3)	Network	120 V single-phase or 2-phase	AC system	TN	Nominal line voltage	Un 120 Vac	Max. AC operating voltage	Uc 150 Vac	Max. load current @25°C	IL 10 A	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 120 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 230 Vac disconnection	Residual Current Leakage current to Ground	Ipe None	Nominal discharge current 15 x 8/20 μs impulses	In 5 kA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax 10 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc 10 kV / 5 kA	Withstand on overvoltages IEEE C62.41.1	10 kV / 10 kA	Protection mode(s)	Common/Differential mode	Protection level L/N @ In (8/20μs)	Up L/N 1.5 kV	Protection level L/PE @ In (8/20μs)	Up L/PE 1.5 kV	Admissible short-circuit current	Iscrc 10 000 A	Mechanical Characteristics		Technology	MOV+GDT	Connection to Network	Screw terminal 2.5 mm ² max. Earthing conductor 2 mm ² - length 60 cm	Mounting	Symmetrical rail 35 mm (EN 60715)	Housing material	Thermoplastic UL94 V-0	Operating temperature	Tu -40/+85°C	Protection rating	IP20	Failsafe mode	Disconnection from AC network	Disconnection indicator	LED green OFF and AC network cut-off	Voltage/operating indicator	Green Led ON	Dimensions	See diagram	Weight	0.062 kg	Disconnectors		Thermal disconnector	Internal	Installation ground fault breaker	Type 'S' or delayed	Standards		Standards compliance	EN 61643-11 / IEC 61643-11	Part number	352922
Electrical Characteristics																																																																									
SPD type	2 (or 3)																																																																								
Network	120 V single-phase or 2-phase																																																																								
AC system	TN																																																																								
Nominal line voltage	Un 120 Vac																																																																								
Max. AC operating voltage	Uc 150 Vac																																																																								
Max. load current @25°C	IL 10 A																																																																								
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 120 Vac withstand																																																																								
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 230 Vac disconnection																																																																								
Residual Current Leakage current to Ground	Ipe None																																																																								
Nominal discharge current 15 x 8/20 μs impulses	In 5 kA																																																																								
Max. discharge current max. withstand @ 8/20 μs by pole	Imax 10 kA																																																																								
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc 10 kV / 5 kA																																																																								
Withstand on overvoltages IEEE C62.41.1	10 kV / 10 kA																																																																								
Protection mode(s)	Common/Differential mode																																																																								
Protection level L/N @ In (8/20μs)	Up L/N 1.5 kV																																																																								
Protection level L/PE @ In (8/20μs)	Up L/PE 1.5 kV																																																																								
Admissible short-circuit current	Iscrc 10 000 A																																																																								
Mechanical Characteristics																																																																									
Technology	MOV+GDT																																																																								
Connection to Network	Screw terminal 2.5 mm ² max. Earthing conductor 2 mm ² - length 60 cm																																																																								
Mounting	Symmetrical rail 35 mm (EN 60715)																																																																								
Housing material	Thermoplastic UL94 V-0																																																																								
Operating temperature	Tu -40/+85°C																																																																								
Protection rating	IP20																																																																								
Failsafe mode	Disconnection from AC network																																																																								
Disconnection indicator	LED green OFF and AC network cut-off																																																																								
Voltage/operating indicator	Green Led ON																																																																								
Dimensions	See diagram																																																																								
Weight	0.062 kg																																																																								
Disconnectors																																																																									
Thermal disconnector	Internal																																																																								
Installation ground fault breaker	Type 'S' or delayed																																																																								
Standards																																																																									
Standards compliance	EN 61643-11 / IEC 61643-11																																																																								
Part number	352922																																																																								
<p>V: Varistor GSG: Specific gas tube LED: Disconnection indicator Ft: Thermal fuse t*: Thermal system disconnection</p>																																																																									

