



CITEL

Compact 1-phase Type 2 (or 3) surge protector - 230 V - Pluggable

DSM215-230



- ↳ Discover our latest innovation : the [DAC15C-11-275](#)
- ↳ Compact single-phase type 2 (or 3) surge protector
- ↳ In : 5 kA
- ↳ Imax : 15 kA
- ↳ Common/Differential mode
- ↳ Pluggable module
- ↳ Remote signaling option
- ↳ EN 61643-11, IEC 61643-11 compliance
- ↳ UL1449 ed.5



| Electrical Characteristics | | |
|--|---------|---|
| SPD type | | 2 (or 3) |
| Network | | 230 V single-phase |
| AC system | | TT-TN |
| Nominal line voltage | Un | 230 Vac |
| Max. AC operating voltage | Uc | 255 Vac |
| Max. load current <i>if series connection</i> | IL | 20 A |
| Temporary Over Voltage (TOV) Characteristics - 5 sec. <i>Without disconnection</i> | UT | 335 Vac withstand |
| Temporary Over Voltage (TOV) Characteristics - 120 mn <i>Without disconnection or with safety disconnection</i> | UT | 440 Vac disconnection |
| Temporary Over Voltage N/PE (TOV HT) <i>Without disconnection or with safety disconnection</i> | UT | 1200 V/300A/200 ms withstand |
| Residual Current <i>Leakage current to Ground</i> | Ipe | None |
| Follow current | If | None |
| Nominal discharge current <i>15 x 8/20 μs impulses</i> | In | 5 kA |
| Max. discharge current <i>max. withstand @ 8/20 μs by pole</i> | Imax | 15 kA |
| Withstand on Combination waveform IEC 61643-11 <i>Class III test: 1.2/50μs - 8/20μs</i> | Uoc | 10 kV |
| Connection mode(s) | | L/N and N/PE |
| Protection mode(s) | | Common/Differential mode |
| Residual voltage at 5 kA <i>@ 5 kA (8/20μs)</i> | Up-5kA | 1.5/0.9 kV |
| Protection level L/N <i>@ In (8/20μs)</i> | Up L/N | 0.9 kV |
| Protection level N/PE <i>@ In (8/20μs)</i> | Up N/PE | 1.5 kV |
| Admissible short-circuit current | Iscsr | 10 000 A |
| Mechanical Characteristics | | |
| Technology | | MOV+GDT |
| SPD configuration | | Single phase |
| Connection to Network | | By screw terminals: 1.5-10mm ² (L/N) or 2.5-25mm ² (PE) |
| Format | | Plug-in modular box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection from AC network |
| Disconnection indicator | | 1 mechanical indicator |
| Spare module(s) | | DSM215-230/G |
| Remote signaling of disconnection | | Option DS215S-230/G : output on changeover contact |
| Disconnectors | | |
| Thermal disconnector | | Internal |
| Installation ground fault breaker | | Type 'S' or delayed |
| Back-up protection device | | 20 A min. - 125 A max. - Fuses type gG |
| Standards | | |
| Standards compliance | | IEC 61643-11 / EN 61643-11 / UL1449 ed.5 |
| Certification | | UL / CSA |
| Part number | | |
| 451700 | | |

