



- ↳ Electrostatic protectors
- ↳ For Class II Led lighting
- ↳ Comply class II safety rules
- ↳ Very compact
- ↳ Plate mounting
- ↳ Wire connection



| Electrical Characteristics | | |
|--|------|--|
| Network | | 220-240 V Single-phase |
| Nominal line voltage | Un | 220-240 Vac |
| Max. AC operating voltage | Uc | 320 Vac |
| Residual Current <i>Leakage current to Ground</i> | Ipe | None |
| Withstand on Combination waveform IEC 61643-11 <i>Class III test: 1.2/50µs - 8/20µs</i> | Uoc | 10 kV / 5 kA |
| Withstand on overvoltages IEEE C62.41.1 | | 10 kV / 10 kA |
| Electrostatic protection level | Uesp | > 0.5 kV |
| Electrostatic protection mode | | N/Functional Earth |
| Mechanical Characteristics | | |
| Connection to Network | | 2 wires (multistrand) of 1mm ² max. |
| Mounting | | On plate |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP67 |
| Remote signaling of disconnection | | No |
| Dimensions | | See diagram |
| Weight | | 0.011 kg |
| Standards | | |
| Certification | | |
| Part number | | |
| 354913 | | |