



CITEL

1-pair DIN rail plug-in Data surge protector

DLA-24DBC



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																																					
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Low Capacity Diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>Fipway, WorldFIP, FieldBus-h2</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>24 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>28 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 20 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. discharge current <i>max. withstand @ 8/20 μs by pole</i></td> <td>I_{max}</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i></td> <td>Up</td> <td>50 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>< 50 pF</td> </tr> <tr> <td>Nominal discharge current <i>C2 Category</i></td> <td>I_n</td> <td>5 kA</td> </tr> <tr> <td>Max. Load current</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>< 4.7 Ohm</td> </tr> </table>		Network		Fipway, WorldFIP, FieldBus-h2	Nominal line voltage	Un	24 V	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 20 MHz	Insertion loss		< 1 dB	Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max}	20 kA	Line inductance		No	Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i>	Up	50 V	Max. capacitance	C	< 50 pF	Nominal discharge current <i>C2 Category</i>	I _n	5 kA	Max. Load current	IL	300 mA	Line resistance		< 4.7 Ohm
Network		Fipway, WorldFIP, FieldBus-h2																																				
Nominal line voltage	Un	24 V																																				
Max. DC operating voltage	Uc	28 Vdc																																				
Max. frequency	f max.	> 20 MHz																																				
Insertion loss		< 1 dB																																				
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max}	20 kA																																				
Line inductance		No																																				
Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i>	Up	50 V																																				
Max. capacitance	C	< 50 pF																																				
Nominal discharge current <i>C2 Category</i>	I _n	5 kA																																				
Max. Load current	IL	300 mA																																				
Line resistance		< 4.7 Ohm																																				
	Mechanical Characteristics																																					
	<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>DLAM-24D3</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> </table>		Technology		GDT+Clamping diode	SPD configuration		1-pair+shielded	Connection to Network		By screw terminal: cross section 0.5-2.5mm ²	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Protection rating		IP20	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Spare module(s)		DLAM-24D3	Dimensions		See diagram						
Technology		GDT+Clamping diode																																				
SPD configuration		1-pair+shielded																																				
Connection to Network		By screw terminal: cross section 0.5-2.5mm ²																																				
Mounting		Symmetrical rail 35 mm (EN 60715)																																				
Housing material		Thermoplastic UL94 V-0																																				
Protection rating		IP20																																				
Failsafe mode		Short-circuit																																				
Disconnection indicator		Transmission interrupt - default mode 2																																				
Spare module(s)		DLAM-24D3																																				
Dimensions		See diagram																																				
	Standards																																					
	Standards compliance IEC 61643-21 / EN 61643-21																																					
	Part number																																					
	640321																																					

