



CITEL



AC/Data surge protector for Led lighting system Class 1

MLP1-230L-P/DL



- Combined surge protector AC and DALI transmission
- Type 2 or 3
- For LED lighting system Class I
- Max. discharge current 10kA
- EN 61643-11, IEC 61643-11 compliance



	Electrical Characteristics																																																																
	<table border="1"> <tr><td>SPD type</td><td></td><td>2+3</td></tr> <tr><td>Network</td><td></td><td>AC: 220-240 V single-phase I Dataline: DALI/DMX/RS485/0-10V</td></tr> <tr><td>AC system</td><td></td><td>TT-TN</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>AC : 230-277 Vac I DATA : 24 Vac</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>AC : 305 Vac I DATA : 28 Vac</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>DATA : 10 MHz</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>AC : 2.5 A I DATA : 300mA</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac disconnection</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>Ipe</td><td>None</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 µs impulses</td><td>In</td><td>AC : 5kA I DATA : 5 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 µs by pole</td><td>Imax</td><td>AC : 10 kA I DATA : 10 kA</td></tr> <tr><td>Total Maximum discharge current max. total withstand @ 8/20 µs</td><td>Imax Total</td><td>AC : 20 kA I DATA : 20 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs</td><td>Uoc</td><td>AC : 10 kV / 5 kA</td></tr> <tr><td>Withstand on overvoltages IEEE C62.41.1</td><td></td><td>10 kV / 10 kA</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level @ In (8/20µs)</td><td>Up</td><td>DATA : 50 V</td></tr> <tr><td>Protection level L/N @ In (8/20µs)</td><td>Up L/N</td><td>1.5 kV</td></tr> <tr><td>Protection level L/PE @ In (8/20µs)</td><td>Up L/PE</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>Iscrr</td><td>10 000 A</td></tr> </table>		SPD type		2+3	Network		AC: 220-240 V single-phase I Dataline: DALI/DMX/RS485/0-10V	AC system		TT-TN	Nominal line voltage	Un	AC : 230-277 Vac I DATA : 24 Vac	Max. AC operating voltage	Uc	AC : 305 Vac I DATA : 28 Vac	Max. frequency	f max.	DATA : 10 MHz	Max. load current @25°C	IL	AC : 2.5 A I DATA : 300mA	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	Residual Current Leakage current to Ground	Ipe	None	Follow current	If	None	Nominal discharge current 15 x 8/20 µs impulses	In	AC : 5kA I DATA : 5 kA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	AC : 10 kA I DATA : 10 kA	Total Maximum discharge current max. total withstand @ 8/20 µs	Imax Total	AC : 20 kA I DATA : 20 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	AC : 10 kV / 5 kA	Withstand on overvoltages IEEE C62.41.1		10 kV / 10 kA	Protection mode(s)		Common/Differential mode	Protection level @ In (8/20µs)	Up	DATA : 50 V	Protection level L/N @ In (8/20µs)	Up L/N	1.5 kV	Protection level L/PE @ In (8/20µs)	Up L/PE	1.5 kV	Admissible short-circuit current	Iscrr	10 000 A
SPD type		2+3																																																															
Network		AC: 220-240 V single-phase I Dataline: DALI/DMX/RS485/0-10V																																																															
AC system		TT-TN																																																															
Nominal line voltage	Un	AC : 230-277 Vac I DATA : 24 Vac																																																															
Max. AC operating voltage	Uc	AC : 305 Vac I DATA : 28 Vac																																																															
Max. frequency	f max.	DATA : 10 MHz																																																															
Max. load current @25°C	IL	AC : 2.5 A I DATA : 300mA																																																															
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																																															
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection																																																															
Residual Current Leakage current to Ground	Ipe	None																																																															
Follow current	If	None																																																															
Nominal discharge current 15 x 8/20 µs impulses	In	AC : 5kA I DATA : 5 kA																																																															
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	AC : 10 kA I DATA : 10 kA																																																															
Total Maximum discharge current max. total withstand @ 8/20 µs	Imax Total	AC : 20 kA I DATA : 20 kA																																																															
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	AC : 10 kV / 5 kA																																																															
Withstand on overvoltages IEEE C62.41.1		10 kV / 10 kA																																																															
Protection mode(s)		Common/Differential mode																																																															
Protection level @ In (8/20µs)	Up	DATA : 50 V																																																															
Protection level L/N @ In (8/20µs)	Up L/N	1.5 kV																																																															
Protection level L/PE @ In (8/20µs)	Up L/PE	1.5 kV																																																															
Admissible short-circuit current	Iscrr	10 000 A																																																															
ELEC																																																																	
Insertion loss		DATA : < 1dB																																																															
Mechanical Characteristics																																																																	
Technology		MOV+GDT																																																															
Connection to Network		AC: Screw terminal - 1.5mm ² max. DATA: Screw terminal - 1mm ² max.																																																															
Mounting		On plate																																																															
Housing material		Thermoplastic UL94 V-0																																																															
Operating temperature		Tu -40/+85°C																																																															
Protection rating		IP20																																																															
Failsafe mode		Disconnection and AC line cut-off																																																															
Disconnection indicator		LED green OFF and AC network cut-off																																																															
Voltage/operating indicator		Green Led ON																																																															
Remote signaling of disconnection		No																																																															
Dimensions		See diagram																																																															
Weight		0.086 kg																																																															
Disconnectors																																																																	
Thermal disconnector		Internal																																																															
Installation ground fault breaker		Type 'S' or delayed																																																															
Standards																																																																	
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																															
Certification																																																																	
Part number																																																																	
721231																																																																	

