




# Type 2 AC surge protector - 1-pole - pluggable

# CITEL

## DAC50S-10-760



- Type 2 AC surge protector
- In: 20 kA
- I<sub>max</sub>: 50 kA
- Pluggable module for each phase
- Remote signaling
- UL1449 ed.5 certified
- EN 61643-11, IEC 61643-11 compliance



Electrical Characteristics	
SPD type	2
Max. AC operating voltage	U <sub>c</sub> 760 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 1000 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 1325 Vac disconnection
Residual Current Leakage current to Ground	I <sub>pe</sub> < 1 mA
Follow current	I <sub>f</sub> None
Nominal discharge current 15 x 8/20 μs impulses	I <sub>n</sub> 20 kA
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub> 50 kA
Protection level @ I <sub>n</sub> (8/20 μs)	U <sub>p</sub> 2.9 kV
Residual voltage at 5 kA @ 5 kA (8/20 μs)	U <sub>p-5kA</sub> 2.6 kV
Admissible short-circuit current	I <sub>sc</sub> 50 000 A
Mechanical Characteristics	
Technology	MOV
SPD configuration	Single phase
Connection to Network	By screw terminals: 2.5-25mm <sup>2</sup>
Format	Plug-in modular box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	T <sub>u</sub> -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from AC network
Disconnection indicator	1 mechanical indicator - Red/Green
Spare module(s)	MDAC50-760
Remote signaling of disconnection	Output on changeover contact
Wiring for remote signaling	1.5 mm <sup>2</sup> max.
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)
Dimensions	See diagram - 1TE (EN43880)
Weight	0.129 kg
Disconnectors	
Thermal disconnector	Internal
Installation ground fault breaker	Type 'S' or delayed
Back-up protection device	50 A min. - 125 A max. - Fuses Type gG
Standards	
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification	OVE / UL
Part number	
821110721	

