





CITEL

Type 2 AC surge protector - 3-phase

DAC50-30-660



- Type 2 AC multipolar surge protector
- In: 20 kA
- Imax: 50 kA
- Pluggable module for each phase
- Remote signaling option
- UL1449 ed.5 compliance
- EN 61643-11, IEC 61643-11 certified



Electrical Characteristics

SPD type	2
Network	600V 3-phase
AC system	TNC
Max. AC operating voltage	Uc 660 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 870 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 1150 Vac disconnection
Residual Current Leakage current to Ground	Ipe < 1 mA
Follow current	If None
Nominal discharge current 15 x 8/20 μ s impulses	In 20 kA
Max. discharge current max. withstand @ 8/20 μ s by pole	Imax 50 kA
Total Maximum discharge current max. total withstand @ 8/20 μ s	Imax Total 150 kA
Protection mode(s)	L/PE
Protection level L/PE @ In (8/20 μ s)	Up L/PE 2.9 kV
Residual voltage L/PE at 5 kA @ 5 kA (8/20 μ s)	Up-5kA 2.4 kV
Admissible short-circuit current	Iscrr 50 000 A

Mechanical Characteristics

Technology	MOV
SPD configuration	3-phase
Connection to Network	By screw terminals: 2.5-25mm ² (35mm ² rigid)
Format	Plug-in modular box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from AC network
Disconnection indicator	1 mechanical indicator by pole - Red/Green
Spare module(s)	MDAC50-660
Remote signaling of disconnection	option DAC50S-30-660 : output on changeover contact
Dimensions	See diagram - 3 TE (EN43880)

Disconnectors

Thermal disconnector	Internal
Installation ground fault breaker	Type 'S' or delayed
Back-up protection device	50 A min. - 125 A max. - Fuses Type gG

Standards

Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification	ÖVE

Part number

821110613

