



Type 2 AC surge protector - 3-phase

CITEL

DACF25-30-320



- ▶ Type 2 AC Multipolar surge protector
- ▶ In : 15 kA
- ▶ I_{max} total : 75 kA
- ▶ Internal Fuse
- ▶ Pluggable module for each phase
- ▶ Remote signaling
- ▶ NF EN 61643-11, IEC 61643-11, UL1449 ed.5 compliance



	Electrical Characteristics																																																
<p>V: High-energy varistor Ft: Thermal fuse F: Overcurrent protection (fuse) t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr><td>SPD type</td><td>IEC</td><td>2</td></tr> <tr><td>Network</td><td></td><td>230/400 V 3-phase</td></tr> <tr><td>AC system</td><td></td><td>TNC</td></tr> <tr><td>Max. AC operating voltage</td><td>U_c</td><td>320 Vac</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac disconnection</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>I_{pe}</td><td>< 1 mA</td></tr> <tr><td>Follow current</td><td>I_f</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>I_n</td><td>15 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>I_{max}</td><td>25 kA</td></tr> <tr><td>Total Maximum discharge current max. total withstand @ 8/20 μs</td><td>I_{max} Total</td><td>75 kA</td></tr> <tr><td>Connection mode(s)</td><td></td><td>L/PE</td></tr> <tr><td>Protection level L/PE @ I_n (8/20 μs)</td><td>U_p L/PE</td><td>1.5 kV</td></tr> <tr><td>Residual voltage L/PE at 5 kA @ 5 kA (8/20 μs)</td><td>U_{p-5kA}</td><td>1.2 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>I_{sc}</td><td>100 000 A</td></tr> </table>	SPD type	IEC	2	Network		230/400 V 3-phase	AC system		TNC	Max. AC operating voltage	U _c	320 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	Residual Current Leakage current to Ground	I _{pe}	< 1 mA	Follow current	I _f	None	Nominal discharge current 15 x 8/20 μs impulses	I _n	15 kA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	25 kA	Total Maximum discharge current max. total withstand @ 8/20 μs	I _{max} Total	75 kA	Connection mode(s)		L/PE	Protection level L/PE @ I _n (8/20 μs)	U _p L/PE	1.5 kV	Residual voltage L/PE at 5 kA @ 5 kA (8/20 μs)	U _{p-5kA}	1.2 kV	Admissible short-circuit current	I _{sc}	100 000 A			
SPD type	IEC	2																																															
Network		230/400 V 3-phase																																															
AC system		TNC																																															
Max. AC operating voltage	U _c	320 Vac																																															
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																															
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection																																															
Residual Current Leakage current to Ground	I _{pe}	< 1 mA																																															
Follow current	I _f	None																																															
Nominal discharge current 15 x 8/20 μs impulses	I _n	15 kA																																															
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	25 kA																																															
Total Maximum discharge current max. total withstand @ 8/20 μs	I _{max} Total	75 kA																																															
Connection mode(s)		L/PE																																															
Protection level L/PE @ I _n (8/20 μs)	U _p L/PE	1.5 kV																																															
Residual voltage L/PE at 5 kA @ 5 kA (8/20 μs)	U _{p-5kA}	1.2 kV																																															
Admissible short-circuit current	I _{sc}	100 000 A																																															
	Mechanical Characteristics																																																
	<table border="1"> <tr><td>Technology</td><td></td><td>MOV</td></tr> <tr><td>SPD configuration</td><td></td><td>3-phase</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminals: 2.5-25mm² (35mm² rigid)</td></tr> <tr><td>Format</td><td></td><td>Plug-in modular box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>T_u</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator by pole - Red/Green</td></tr> <tr><td>Spare module(s)</td><td></td><td>MDACF25-320</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>option DACF25S-30-320 : output on changeover contact</td></tr> <tr><td>Wiring for remote signaling</td><td></td><td>1.5 mm² max.</td></tr> <tr><td>Max. Voltage/Current for remote signaling</td><td></td><td>250 V / 0.5 A (AC) / 30 V / 3 A (DC)</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram - 3 TE (EN43880)</td></tr> <tr><td>Weight</td><td></td><td>0.300 kg</td></tr> </table>	Technology		MOV	SPD configuration		3-phase	Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)	Format		Plug-in modular box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	T _u	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection from AC network	Disconnection indicator		1 mechanical indicator by pole - Red/Green	Spare module(s)		MDACF25-320	Remote signaling of disconnection		option DACF25S-30-320 : output on changeover contact	Wiring for remote signaling		1.5 mm ² max.	Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)	Dimensions		See diagram - 3 TE (EN43880)	Weight		0.300 kg
Technology		MOV																																															
SPD configuration		3-phase																																															
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)																																															
Format		Plug-in modular box																																															
Mounting		Symmetrical rail 35 mm (EN 60715)																																															
Housing material		Thermoplastic UL94 V-0																																															
Operating temperature	T _u	-40/+85°C																																															
Protection rating		IP20																																															
Failsafe mode		Disconnection from AC network																																															
Disconnection indicator		1 mechanical indicator by pole - Red/Green																																															
Spare module(s)		MDACF25-320																																															
Remote signaling of disconnection		option DACF25S-30-320 : output on changeover contact																																															
Wiring for remote signaling		1.5 mm ² max.																																															
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)																																															
Dimensions		See diagram - 3 TE (EN43880)																																															
Weight		0.300 kg																																															
	Disconnectors																																																
	<table border="1"> <tr><td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td></td><td>Type 'S' or delayed</td></tr> <tr><td>Back-up protection device</td><td></td><td>internal (equivalent AC rating : 40 A, gG Type)</td></tr> </table>	Thermal disconnector		Internal	Installation ground fault breaker		Type 'S' or delayed	Back-up protection device		internal (equivalent AC rating : 40 A, gG Type)																																							
Thermal disconnector		Internal																																															
Installation ground fault breaker		Type 'S' or delayed																																															
Back-up protection device		internal (equivalent AC rating : 40 A, gG Type)																																															
	Standards																																																
	<table border="1"> <tr><td>Standards compliance</td><td></td><td>IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td></tr> </table>	Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																													
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																															
	Part number																																																
	821410313																																																

