



DS252VG-300/G



- › Type 1+2+3 unipolar surge protector
- › 25 kA on 10/350µs impulse
- › Low voltage Up
- › Internal disconnection, status indicator and remote signaling
- › Optimized to TOV
- › IEC 61643-11 compliance
- › UL1449 ed.5 recognition



	Electrical Characteristics																																																																									
 <p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>1+2+3</td></tr> <tr><td>Network</td><td></td><td>230 V single-phase</td></tr> <tr><td>AC system</td><td></td><td>TT-TN</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>230 Vac</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>255 Vac</td></tr> <tr><td>Max. load current if series connection</td><td>IL</td><td>100 A</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>580 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>770 Vac withstand</td></tr> <tr><td>Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection</td><td>UT</td><td>1200 V/300A/200 ms withstand</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>Ipe</td><td>None</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 µs impulses</td><td>In</td><td>30 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 µs by pole</td><td>Imax</td><td>70 kA</td></tr> <tr><td>Impulse current by pole max. withstand 10/350µs by pole</td><td>Iimp</td><td>25 kA</td></tr> <tr><td>Total lightning current max. total withstand @ 10/350µs</td><td>Itotal</td><td>50 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs</td><td>Uoc</td><td>20 kV</td></tr> <tr><td>Withstand on overvoltages IEEE C62.41.1</td><td></td><td>20 kV</td></tr> <tr><td>Specific energy by pole max. withstand 10/350 µs</td><td>W/R</td><td>156 kJ/ohm</td></tr> <tr><td>Connection mode(s)</td><td></td><td>L/N and N/PE</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Residual voltage @ In (8/20 µs)</td><td>Up-in</td><td>1.1 kV</td></tr> <tr><td>Protection level L/N @ In (8/20µs)</td><td>Up L/N</td><td>1.5 kV</td></tr> <tr><td>Protection level N/PE @ In (8/20µs)</td><td>Up N/PE</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>Iscrr</td><td>50 000 A</td></tr> </table>		SPD type		1+2+3	Network		230 V single-phase	AC system		TT-TN	Nominal line voltage	Un	230 Vac	Max. AC operating voltage	Uc	255 Vac	Max. load current if series connection	IL	100 A	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	580 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	770 Vac withstand	Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT	1200 V/300A/200 ms withstand	Residual Current Leakage current to Ground	Ipe	None	Follow current	If	None	Nominal discharge current 15 x 8/20 µs impulses	In	30 kA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	70 kA	Impulse current by pole max. withstand 10/350µs by pole	Iimp	25 kA	Total lightning current max. total withstand @ 10/350µs	Itotal	50 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	20 kV	Withstand on overvoltages IEEE C62.41.1		20 kV	Specific energy by pole max. withstand 10/350 µs	W/R	156 kJ/ohm	Connection mode(s)		L/N and N/PE	Protection mode(s)		Common/Differential mode	Residual voltage @ In (8/20 µs)	Up-in	1.1 kV	Protection level L/N @ In (8/20µs)	Up L/N	1.5 kV	Protection level N/PE @ In (8/20µs)	Up N/PE	1.5 kV	Admissible short-circuit current	Iscrr	50 000 A
SPD type		1+2+3																																																																								
Network		230 V single-phase																																																																								
AC system		TT-TN																																																																								
Nominal line voltage	Un	230 Vac																																																																								
Max. AC operating voltage	Uc	255 Vac																																																																								
Max. load current if series connection	IL	100 A																																																																								
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	580 Vac withstand																																																																								
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	770 Vac withstand																																																																								
Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT	1200 V/300A/200 ms withstand																																																																								
Residual Current Leakage current to Ground	Ipe	None																																																																								
Follow current	If	None																																																																								
Nominal discharge current 15 x 8/20 µs impulses	In	30 kA																																																																								
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	70 kA																																																																								
Impulse current by pole max. withstand 10/350µs by pole	Iimp	25 kA																																																																								
Total lightning current max. total withstand @ 10/350µs	Itotal	50 kA																																																																								
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	20 kV																																																																								
Withstand on overvoltages IEEE C62.41.1		20 kV																																																																								
Specific energy by pole max. withstand 10/350 µs	W/R	156 kJ/ohm																																																																								
Connection mode(s)		L/N and N/PE																																																																								
Protection mode(s)		Common/Differential mode																																																																								
Residual voltage @ In (8/20 µs)	Up-in	1.1 kV																																																																								
Protection level L/N @ In (8/20µs)	Up L/N	1.5 kV																																																																								
Protection level N/PE @ In (8/20µs)	Up N/PE	1.5 kV																																																																								
Admissible short-circuit current	Iscrr	50 000 A																																																																								
Mechanical Characteristics																																																																										
<table border="1"> <tr><td>Technology</td><td>VG Technology (MOV+GSG)</td></tr> <tr><td>SPD configuration</td><td>Single phase</td></tr> <tr><td>Connection to Network</td><td>By screw terminals: 6-35mm² / by bus</td></tr> <tr><td>Format</td><td>1-pole modular box assembled</td></tr> <tr><td>Mounting</td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu -40/+85°C</td></tr> <tr><td>Protection rating</td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td>1 mechanical indicator by pole</td></tr> <tr><td>Remote signaling of disconnection</td><td>Output on changeover contact</td></tr> <tr><td>Dimensions</td><td>See diagram</td></tr> </table>		Technology	VG Technology (MOV+GSG)	SPD configuration	Single phase	Connection to Network	By screw terminals: 6-35mm ² / by bus	Format	1-pole modular box assembled	Mounting	Symmetrical rail 35 mm (EN 60715)	Housing material	Thermoplastic UL94 V-0	Operating temperature	Tu -40/+85°C	Protection rating	IP20	Failsafe mode	Disconnection from AC network	Disconnection indicator	1 mechanical indicator by pole	Remote signaling of disconnection	Output on changeover contact	Dimensions	See diagram																																																	
Technology	VG Technology (MOV+GSG)																																																																									
SPD configuration	Single phase																																																																									
Connection to Network	By screw terminals: 6-35mm ² / by bus																																																																									
Format	1-pole modular box assembled																																																																									
Mounting	Symmetrical rail 35 mm (EN 60715)																																																																									
Housing material	Thermoplastic UL94 V-0																																																																									
Operating temperature	Tu -40/+85°C																																																																									
Protection rating	IP20																																																																									
Failsafe mode	Disconnection from AC network																																																																									
Disconnection indicator	1 mechanical indicator by pole																																																																									
Remote signaling of disconnection	Output on changeover contact																																																																									
Dimensions	See diagram																																																																									
Disconnectors																																																																										
<table border="1"> <tr><td>Thermal disconnector</td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td>Type 'S' or delayed</td></tr> <tr><td>Fuses</td><td>Fuse assembly: SFD1-25-11S / or Fuses Type gG 315 A</td></tr> </table>		Thermal disconnector	Internal	Installation ground fault breaker	Type 'S' or delayed	Fuses	Fuse assembly: SFD1-25-11S / or Fuses Type gG 315 A																																																																			
Thermal disconnector	Internal																																																																									
Installation ground fault breaker	Type 'S' or delayed																																																																									
Fuses	Fuse assembly: SFD1-25-11S / or Fuses Type gG 315 A																																																																									
Standards																																																																										
<table border="1"> <tr><td>Standards compliance</td><td>IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td></tr> <tr><td>Certification</td><td>UL Recognized</td></tr> </table>		Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5	Certification	UL Recognized																																																																					
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																																									
Certification	UL Recognized																																																																									
Part number																																																																										
3403																																																																										