



## 2-pair monobloc Data surge protector

# CITEL

## DLU2-06DBC



- For DIN rail mounting
- Monobloc housing
- 2-pair
- Un: 6 V
- IEC 61643-21 compliance
- UL497A certified



	<b>Electrical Characteristics</b>																																											
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>6 V line, High bitrate, MIC/T2, 10BaseT</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>6 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>10 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>&gt; 20 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>&lt; 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection mode(s)</td> <td></td> <td>Common/Differential mode</td> </tr> <tr> <td>Protection level Following the test category C3 (IEC61643-21) - Line/Line</td> <td>Up</td> <td>25 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>&lt; 25 pF</td> </tr> <tr> <td>Impulse current 2 x 10/350μs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In</td> <td>5 kA</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>&lt; 4.7 Ohm</td> </tr> </table>		Network		6 V line, High bitrate, MIC/T2, 10BaseT	Nominal line voltage	Un	6 V	Max. DC operating voltage	Uc	10 Vdc	Max. frequency	f max.	> 20 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		No	Protection mode(s)		Common/Differential mode	Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	25 V	Max. capacitance	C	< 25 pF	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA	Nominal discharge current C2 Category	In	5 kA	Line resistance		< 4.7 Ohm
Network		6 V line, High bitrate, MIC/T2, 10BaseT																																										
Nominal line voltage	Un	6 V																																										
Max. DC operating voltage	Uc	10 Vdc																																										
Max. frequency	f max.	> 20 MHz																																										
Insertion loss		< 1 dB																																										
Max. load current @25°C	IL	300 mA																																										
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																										
Line inductance		No																																										
Protection mode(s)		Common/Differential mode																																										
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	25 V																																										
Max. capacitance	C	< 25 pF																																										
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA																																										
Nominal discharge current C2 Category	In	5 kA																																										
Line resistance		< 4.7 Ohm																																										
<b>Mechanical Characteristics</b>																																												
		GDT+Clamping diode																																										
		SPD configuration 2 pairs																																										
		Connection to Network By screw terminal - cross section 1.5-2.5mm <sup>2</sup>																																										
		Format DIN box																																										
		Mounting Symmetrical rail 35 mm (EN 60715)																																										
		Housing material Thermoplastic UL94 V-0																																										
		Operating temperature Tu -40/+85°C																																										
		Protection rating IP20																																										
		Failsafe mode Short-circuit																																										
		Disconnection indicator Transmission interrupt - default mode 2																																										
		Remote signaling of disconnection No																																										
		Dimensions See diagram																																										
		Weight 0.063 kg																																										
<b>Standards</b>																																												
		Standards compliance IEC 61643-21 / EN 61643-21 / UL497A																																										
		Certification UL 497B																																										
<b>Part number</b>																																												
640431																																												

