



CITEL

1-pair DIN rail plug-in Data surge protector

DLA-48D3/R



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



Electrical Characteristics

Network		RNIS-T0, 48 V line
Nominal line voltage	Un	48 V
Max. DC operating voltage	Uc	53 Vdc
Max. frequency	f max.	> 3 MHz
Insertion loss		< 1 dB
Max. load current @25°C	IL	300 mA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA
Line inductance (± 10%)		non
Protection level @ In (8/20 μs)	Up L/L	70 V
Max. capacitance	C	< 50 pF
Impulse current 2 x 10/350 μs Test - D1 Category	limp	5 kA
Nominal discharge current C2 Category	In	5 kA
Line resistance (± 10%)		4.7 Ohm

Mechanical Characteristics



Technology		GDT+Clamping diode
SPD configuration		1-pair+shielded
Connection to Network		Spring terminal: cross section 0.5-2.5mm ²
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating and storage temperature		-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit
Disconnection indicator		Transmission interrupt - default mode 2
Spare module(s)		DLAM-48D3
Dimensions		See diagram

Standards

Standards compliance		IEC 61643-21 / EN 61643-21
----------------------	--	----------------------------

Part number

Part number		6403024
-------------	--	---------



G: 3-electrode gas tube
 Gb: 2-electrode gas tube
 R: Resistor
 D: Clamping diode

