



# CITEL

## 1-pair DIN rail plug-in Data surge protector

### DLA-24D3/R



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	<b>Electrical Characteristics</b>	
	Network	4-20 mA
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	Nominal line voltage	Un 24 V
	Max. DC operating voltage	Uc 28 Vdc
	Max. frequency	f max. > 3 MHz
	Insertion loss	< 1 dB
	Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I <sub>max</sub> 20 kA
	Line inductance	No
	Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i>	Up 40 V
	Max. capacitance	C < 50 pF
	Impulse current <i>2 x 10/350 μs Test - D1 Category</i>	I <sub>imp</sub> 5 kA
	Nominal discharge current <i>C2 Category</i>	I <sub>n</sub> 5 kA
	Max. Load current	IL 300 mA
	Line resistance	< 4.7 Ohm
	<b>Mechanical Characteristics</b>	
	Technology	GDT+Clamping diode
SPD configuration	1-pair+shielded	
Connection to Network	Spring terminal: cross section 0.5-2.5mm <sup>2</sup>	
Mounting	Symmetrical rail 35 mm (EN 60715)	
Housing material	Thermoplastic UL94 V-0	
Operating and storage temperature	-40/+85°C	
Protection rating	IP20	
Failsafe mode	Short-circuit	
Disconnection indicator	Transmission interrupt - default mode 2	
Spare module(s)	DLAM-24D3	
Dimensions	See diagram	
<b>Standards</b>		
Standards compliance	IEC 61643-21 / EN 61643-21	
<b>Part number</b>		
6401034		

