



CITEL

1-pair DIN rail plug-in Data surge protector

DLA-06D3/R



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																																								
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RS422, RS485</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>6 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>8 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. discharge current <i>max. withstand @ 8/20 μs by pole</i></td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10%)</td> <td></td> <td>non</td> </tr> <tr> <td>Protection level <i>@ In (8/20 μs)</i></td> <td>Up L/L</td> <td>20 V</td> </tr> <tr> <td>Protection level <i>@ In (8/20 μs)</i></td> <td>Up L/PE</td> <td>20 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>< 50 pF</td> </tr> <tr> <td>Impulse current <i>2 x 10/350 μs Test - D1 Category</i></td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current <i>C2 Category</i></td> <td>In</td> <td>5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>4.7 Ohm</td> </tr> </table>		Network		RS422, RS485	Nominal line voltage	Un	6 V	Max. DC operating voltage	Uc	8 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	Imax	20 kA	Line inductance (± 10%)		non	Protection level <i>@ In (8/20 μs)</i>	Up L/L	20 V	Protection level <i>@ In (8/20 μs)</i>	Up L/PE	20 V	Max. capacitance	C	< 50 pF	Impulse current <i>2 x 10/350 μs Test - D1 Category</i>	Iimp	5 kA	Nominal discharge current <i>C2 Category</i>	In	5 kA	Line resistance (± 10%)		4.7 Ohm
Network		RS422, RS485																																							
Nominal line voltage	Un	6 V																																							
Max. DC operating voltage	Uc	8 Vdc																																							
Max. frequency	f max.	> 3 MHz																																							
Insertion loss		< 1 dB																																							
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	Imax	20 kA																																							
Line inductance (± 10%)		non																																							
Protection level <i>@ In (8/20 μs)</i>	Up L/L	20 V																																							
Protection level <i>@ In (8/20 μs)</i>	Up L/PE	20 V																																							
Max. capacitance	C	< 50 pF																																							
Impulse current <i>2 x 10/350 μs Test - D1 Category</i>	Iimp	5 kA																																							
Nominal discharge current <i>C2 Category</i>	In	5 kA																																							
Line resistance (± 10%)		4.7 Ohm																																							
Mechanical Characteristics																																									
<table border="1"> <tr> <td>Technology</td> <td colspan="2">GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td colspan="2">1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">Spring terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Mounting</td> <td colspan="2">Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td colspan="2">Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating and storage temperature</td> <td colspan="2">-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td colspan="2">IP20</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td colspan="2">Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td colspan="2">DLAM-06D3</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">See diagram</td> </tr> </table>			Technology	GDT+Clamping diode		SPD configuration	1-pair+shielded		Connection to Network	Spring terminal: cross section 0.5-2.5mm ²		Mounting	Symmetrical rail 35 mm (EN 60715)		Housing material	Thermoplastic UL94 V-0		Operating and storage temperature	-40/+85°C		Protection rating	IP20		Failsafe mode	Short-circuit		Disconnection indicator	Transmission interrupt - default mode 2		Spare module(s)	DLAM-06D3		Dimensions	See diagram							
Technology	GDT+Clamping diode																																								
SPD configuration	1-pair+shielded																																								
Connection to Network	Spring terminal: cross section 0.5-2.5mm ²																																								
Mounting	Symmetrical rail 35 mm (EN 60715)																																								
Housing material	Thermoplastic UL94 V-0																																								
Operating and storage temperature	-40/+85°C																																								
Protection rating	IP20																																								
Failsafe mode	Short-circuit																																								
Disconnection indicator	Transmission interrupt - default mode 2																																								
Spare module(s)	DLAM-06D3																																								
Dimensions	See diagram																																								
Standards																																									
Standards compliance		IEC 61643-21 / EN 61643-21																																							
Part number																																									
6401014																																									

