




- Surge protector for DC supplies 2-pole
- Type 1 + 2
- In: 15 kA / I<sub>max</sub>: 30 kA
- I<sub>imp</sub>: 4kA
- Pluggable module
- Remote signaling (option)
- prIEC 61643-41 compliance



Electrical Characteristics	
SPD type	1+2
Nominal DC voltage	Un-dc 48 Vdc
Max. AC operating voltage	Uc 50 Vac
Max. DC operating voltage	Uc 65 Vdc
Residual Current Leakage current to Ground	I <sub>pe</sub> < 0.1 mA
Follow current	I <sub>f</sub> None
Nominal discharge current 15 x 8/20 μs impulses	I <sub>n</sub> 15 kA
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub> 30 kA
Impulse current by pole max. withstand 10/350 μs by pole	I <sub>imp</sub> 4 kA
Total lightning current max. total withstand @ 10/350 μs	I <sub>total</sub> 8 kA
Connection mode(s)	+/-PE and -/PE
Protection level +/-PE (-/PE) @ I <sub>n</sub> (8/20 μs)	U <sub>p</sub> 300 V / 600 V
Admissible short-circuit current	I <sub>sc</sub> 50 000 A
Mechanical Characteristics	
Technology	MOV
SPD configuration	2-poles
Connection to Network	Screw terminals: 2.5-25mm <sup>2</sup> +/- 1.5-10mm <sup>2</sup>
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	T <sub>u</sub> -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from AC network
Disconnection indicator	2 mechanical indicators - Red/Green
Spare module(s)	MDDC30-65
Remote signaling of disconnection	Option DDC30S-20-65: output on changeover contact
Wiring for remote signaling	1.5 mm <sup>2</sup> max.
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)
Dimensions	See diagram - 2TE (EN43880)
Weight	0.167 kg
Disconnectors	
Thermal disconnector	Internal
Back-up protection device	50 A min. - 125 A max. - Fuses Type gG
Standards	
Standards compliance	prIEC 61643-41
Part number	
828110112	

