



2-pair monobloc Data surge protector

CITEL

DLU2-12D3



- For DIN rail mounting
- Monobloc housing
- 2-pair
- Un: 12 V
- IEC 61643-21 compliance
- UL497A



	Electrical Characteristics																																											
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>Profibus-FMS, Interbus, FieldBus-H1, Batibus, RS232, RS485</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>12 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>15 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection mode(s)</td> <td></td> <td>Common/Differential mode</td> </tr> <tr> <td>Protection level Following the test category C3 (IEC61643-21) - Line/Line</td> <td>Up</td> <td>30 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>< 50 pF</td> </tr> <tr> <td>Impulse current 2 x 10/350μs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In</td> <td>5 kA</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>< 4.7 Ohm</td> </tr> </table>		Network		Profibus-FMS, Interbus, FieldBus-H1, Batibus, RS232, RS485	Nominal line voltage	Un	12 V	Max. DC operating voltage	Uc	15 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		No	Protection mode(s)		Common/Differential mode	Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	30 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA	Nominal discharge current C2 Category	In	5 kA	Line resistance		< 4.7 Ohm
Network		Profibus-FMS, Interbus, FieldBus-H1, Batibus, RS232, RS485																																										
Nominal line voltage	Un	12 V																																										
Max. DC operating voltage	Uc	15 Vdc																																										
Max. frequency	f max.	> 3 MHz																																										
Insertion loss		< 1 dB																																										
Max. load current @25°C	IL	300 mA																																										
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																										
Line inductance		No																																										
Protection mode(s)		Common/Differential mode																																										
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	30 V																																										
Max. capacitance	C	< 50 pF																																										
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA																																										
Nominal discharge current C2 Category	In	5 kA																																										
Line resistance		< 4.7 Ohm																																										
Mechanical Characteristics																																												
<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>2 pairs</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal - cross section 1.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td></td> <td>DIN box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Remote signaling of disconnection</td> <td></td> <td>No</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td></td> <td>0.064 kg</td> </tr> </table>			Technology		GDT+Clamping diode	SPD configuration		2 pairs	Connection to Network		By screw terminal - cross section 1.5-2.5mm ²	Format		DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Remote signaling of disconnection		No	Dimensions		See diagram	Weight		0.064 kg			
Technology		GDT+Clamping diode																																										
SPD configuration		2 pairs																																										
Connection to Network		By screw terminal - cross section 1.5-2.5mm ²																																										
Format		DIN box																																										
Mounting		Symmetrical rail 35 mm (EN 60715)																																										
Housing material		Thermoplastic UL94 V-0																																										
Operating temperature	Tu	-40/+85°C																																										
Protection rating		IP20																																										
Failsafe mode		Short-circuit																																										
Disconnection indicator		Transmission interrupt - default mode 2																																										
Remote signaling of disconnection		No																																										
Dimensions		See diagram																																										
Weight		0.064 kg																																										
Standards																																												
<table border="1"> <tr> <td>Standards compliance</td> <td></td> <td>IEC 61643-21 / EN 61643-21 / UL497A</td> </tr> <tr> <td>Certification</td> <td></td> <td>UL 497B</td> </tr> </table>			Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A	Certification		UL 497B																																				
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A																																										
Certification		UL 497B																																										
Part number																																												
640403																																												

