



MJ8-C6A



- ↳ up to 10-Gigabit Ethernet compatible
- ↳ Category 6A compatible
- ↳ RJ45 Shielded connectors
- ↳ Mounted on frame or DIN rail
- ↳ Compliance IEC 61643-21, EN 61643-21
- ↳ Certified UL497B



	Electrical Characteristics																																											
 <p style="text-align: center;">G: 3-electrode GDT DBC: 3-pole Low capacitance diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>10Gigabit Ethernet - Cat 6A cabling specification</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>5 Vdc</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>8 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>500 MHz</td> </tr> <tr> <td>Max. data rate</td> <td></td> <td>10 Gbps</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Protection level</td> <td>Up</td> <td>20 V</td> </tr> <tr> <td colspan="3"><i>Following the test category C3 (IEC61643-21) - Line/Line</i></td> </tr> <tr> <td>Impulse current</td> <td>Iimp</td> <td>500 A</td> </tr> <tr> <td colspan="3"><i>2 x 10/350µs Test - D1 Category</i></td> </tr> <tr> <td>Line/Line Nominal discharge current</td> <td>In L/L</td> <td>500 A</td> </tr> <tr> <td colspan="3"><i>C2 Category</i></td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth)</td> <td>In L/PE</td> <td>2000 A</td> </tr> <tr> <td colspan="3"><i>8/20µs Test x 10 - C2 Category</i></td> </tr> </table>		Network		10Gigabit Ethernet - Cat 6A cabling specification	Nominal line voltage	Un	5 Vdc	Max. DC operating voltage	Uc	8 Vdc	Max. frequency	f max.	500 MHz	Max. data rate		10 Gbps	Insertion loss		< 1 dB	Protection level	Up	20 V	<i>Following the test category C3 (IEC61643-21) - Line/Line</i>			Impulse current	Iimp	500 A	<i>2 x 10/350µs Test - D1 Category</i>			Line/Line Nominal discharge current	In L/L	500 A	<i>C2 Category</i>			Nominal Discharge Current, X-C (Line/Earth)	In L/PE	2000 A	<i>8/20µs Test x 10 - C2 Category</i>		
Network		10Gigabit Ethernet - Cat 6A cabling specification																																										
Nominal line voltage	Un	5 Vdc																																										
Max. DC operating voltage	Uc	8 Vdc																																										
Max. frequency	f max.	500 MHz																																										
Max. data rate		10 Gbps																																										
Insertion loss		< 1 dB																																										
Protection level	Up	20 V																																										
<i>Following the test category C3 (IEC61643-21) - Line/Line</i>																																												
Impulse current	Iimp	500 A																																										
<i>2 x 10/350µs Test - D1 Category</i>																																												
Line/Line Nominal discharge current	In L/L	500 A																																										
<i>C2 Category</i>																																												
Nominal Discharge Current, X-C (Line/Earth)	In L/PE	2000 A																																										
<i>8/20µs Test x 10 - C2 Category</i>																																												
Mechanical Characteristics																																												
<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>4 pairs+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>RJ45 shielded connectors Female input/output</td> </tr> <tr> <td>Format</td> <td></td> <td>Connector RJ45</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Mounting flange,Screw lug, DIN Rail</td> </tr> <tr> <td>Accessory(s) provided</td> <td></td> <td>DIN rail adapter, screw, screw nut, earthing plate, countersunk screw, cable shoe</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Aluminium</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Pinout</td> <td></td> <td>(1-2)(3-6)(4-5)(7-8)</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td></td> <td>0.106 kg</td> </tr> </table>			Technology		GDT+Clamping diode	SPD configuration		4 pairs+shielded	Connection to Network		RJ45 shielded connectors Female input/output	Format		Connector RJ45	Mounting		Mounting flange,Screw lug, DIN Rail	Accessory(s) provided		DIN rail adapter, screw, screw nut, earthing plate, countersunk screw, cable shoe	Housing material		Aluminium	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Pinout		(1-2)(3-6)(4-5)(7-8)	Dimensions		See diagram	Weight		0.106 kg
Technology		GDT+Clamping diode																																										
SPD configuration		4 pairs+shielded																																										
Connection to Network		RJ45 shielded connectors Female input/output																																										
Format		Connector RJ45																																										
Mounting		Mounting flange,Screw lug, DIN Rail																																										
Accessory(s) provided		DIN rail adapter, screw, screw nut, earthing plate, countersunk screw, cable shoe																																										
Housing material		Aluminium																																										
Operating temperature	Tu	-40/+85°C																																										
Protection rating		IP20																																										
Failsafe mode		Short-circuit																																										
Disconnection indicator		Transmission interrupt - default mode 2																																										
Pinout		(1-2)(3-6)(4-5)(7-8)																																										
Dimensions		See diagram																																										
Weight		0.106 kg																																										
Standards																																												
<table border="1"> <tr> <td>Standards compliance</td> <td></td> <td>IEC 61643-21 / EN 61643-21 / UL497B IEEE 802-3af/3at/3bt/ANSI/TIA-568-C.1</td> </tr> <tr> <td>Certification</td> <td></td> <td>UL 497B</td> </tr> </table>			Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B IEEE 802-3af/3at/3bt/ANSI/TIA-568-C.1	Certification		UL 497B																																				
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B IEEE 802-3af/3at/3bt/ANSI/TIA-568-C.1																																										
Certification		UL 497B																																										
Part number																																												
581540																																												