



# CITEL

## 1-pair DIN rail plug-in Data surge protector

### DLAS1-24D3



- 1-pair Pluggable SPD for dataline
- Visual indicator in failsafe behaviour
- Without line cut-off
- Line voltage 24 Vdc
- Din rail mounting, Screw terminals
- IEC/EN 61643-21 and UL497A compliance



	<b>Electrical Characteristics</b>																																		
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube PTC: Thermal resistor R: Resistor D : Clamping diode Vi : Indicator</p>	<table border="1"> <tr><td>Network</td><td></td><td>4-20 mA</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>28 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>&gt; 3 MHz</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>300 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Line inductance</td><td></td><td>No</td></tr> <tr><td>Protection level Following the test category C3 (IEC61643-21) - Line/Line</td><td>Up</td><td>40 V</td></tr> <tr><td>Impulse current 2 x 10/350 μs Test - D1 Category</td><td>Iimp</td><td>5 kA</td></tr> <tr><td>Line/Line Nominal discharge current C2 Category</td><td>In L/L</td><td>5 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category</td><td>In L/PE</td><td>5 kA</td></tr> <tr><td>Line resistance</td><td></td><td>&lt; 4.7 Ohm</td></tr> </table>		Network		4-20 mA	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 3 MHz	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		No	Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	40 V	Impulse current 2 x 10/350 μs Test - D1 Category	Iimp	5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	In L/PE	5 kA	Line resistance		< 4.7 Ohm
Network		4-20 mA																																	
Max. DC operating voltage	Uc	28 Vdc																																	
Max. frequency	f max.	> 3 MHz																																	
Max. load current @25°C	IL	300 mA																																	
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																	
Line inductance		No																																	
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	40 V																																	
Impulse current 2 x 10/350 μs Test - D1 Category	Iimp	5 kA																																	
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																	
Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	In L/PE	5 kA																																	
Line resistance		< 4.7 Ohm																																	
<b>ELEC</b>																																			
Nominal line voltage		Un 24 V																																	
<b>Mechanical Characteristics</b>																																			
Technology		GDT+Clamping diode+PTC (thermal resistor) + Resistor																																	
SPD configuration		1-pair+shielded																																	
Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>																																	
Format		Plug-in DIN box																																	
Mounting		Symmetrical rail 35 mm (EN 60715)																																	
Housing material		Thermoplastic UL94 V-0																																	
Operating temperature		Tu -40/+85°C																																	
Protection rating		IP20																																	
Failsafe mode		Opening line - transmission cut-off - fault mode 2																																	
Disconnection indicator		Visual indicator is red																																	
Spare module(s)		DLAS1M-24D3																																	
Dimensions		See diagram																																	
<b>Standards</b>																																			
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A																																	
Certification		UL Listed																																	
<b>Part number</b>																																			
6415031																																			

