



1-pair DIN rail plug-in Data surge protector

CITEL

DLAS1-24D3



- 1-pair Pluggable SPD for dataline
- Visual indicator in failsafe behaviour
- Without line cut-off
- Line voltage 24 Vdc
- Din rail mounting, Screw terminals
- IEC/EN 61643-21 and UL497A compliance



	Electrical Characteristics																																					
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube PTC: Thermal resistor R: Resistor D : Clamping diode Vi : Indicator</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>4-20 mA</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>28 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>I_{max}</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td></td> <td>non</td> </tr> <tr> <td>Protection level @ I_n (8/20 μs)</td> <td>Up L/L</td> <td>40 V</td> </tr> <tr> <td>Impulse current 2 x 10/350 μs Test - D1 Category</td> <td>I_{imp}</td> <td>5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>I_n L/L</td> <td>5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category</td> <td>I_n L/PE</td> <td>5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>4.7 Ohm</td> </tr> </table>		Network		4-20 mA	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 3 MHz	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA	Line inductance (± 10 %)		non	Protection level @ I _n (8/20 μs)	Up L/L	40 V	Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA	Line/Line Nominal discharge current C2 Category	I _n L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	I _n L/PE	5 kA	Line resistance (± 10%)		4.7 Ohm			
Network		4-20 mA																																				
Max. DC operating voltage	Uc	28 Vdc																																				
Max. frequency	f max.	> 3 MHz																																				
Max. load current @25°C	IL	300 mA																																				
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA																																				
Line inductance (± 10 %)		non																																				
Protection level @ I _n (8/20 μs)	Up L/L	40 V																																				
Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA																																				
Line/Line Nominal discharge current C2 Category	I _n L/L	5 kA																																				
Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	I _n L/PE	5 kA																																				
Line resistance (± 10%)		4.7 Ohm																																				
ELEC																																						
	<table border="1"> <tr> <td>Nominal line voltage</td> <td>U_n</td> <td>24 V</td> </tr> </table>	Nominal line voltage	U _n	24 V																																		
Nominal line voltage	U _n	24 V																																				
Mechanical Characteristics																																						
	<table border="1"> <tr> <td>Technology</td> <td colspan="2">GDT+Clamping diode+PTC (thermal resistor) + Resistor</td> </tr> <tr> <td>SPD configuration</td> <td colspan="2">1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">By screw terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td colspan="2">Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td colspan="2">Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td colspan="2">Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>T_u</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td colspan="2">IP20</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Opening line - transmission cut-off - fault mode 2</td> </tr> <tr> <td>Disconnection indicator</td> <td colspan="2">Visual indicator is red</td> </tr> <tr> <td>Spare module(s)</td> <td colspan="2">DLAS1M-24D3</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">See diagram</td> </tr> </table>		Technology	GDT+Clamping diode+PTC (thermal resistor) + Resistor		SPD configuration	1-pair+shielded		Connection to Network	By screw terminal: cross section 0.5-2.5mm ²		Format	Plug-in DIN box		Mounting	Symmetrical rail 35 mm (EN 60715)		Housing material	Thermoplastic UL94 V-0		Operating temperature	T _u	-40/+85°C	Protection rating	IP20		Failsafe mode	Opening line - transmission cut-off - fault mode 2		Disconnection indicator	Visual indicator is red		Spare module(s)	DLAS1M-24D3		Dimensions	See diagram	
Technology	GDT+Clamping diode+PTC (thermal resistor) + Resistor																																					
SPD configuration	1-pair+shielded																																					
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²																																					
Format	Plug-in DIN box																																					
Mounting	Symmetrical rail 35 mm (EN 60715)																																					
Housing material	Thermoplastic UL94 V-0																																					
Operating temperature	T _u	-40/+85°C																																				
Protection rating	IP20																																					
Failsafe mode	Opening line - transmission cut-off - fault mode 2																																					
Disconnection indicator	Visual indicator is red																																					
Spare module(s)	DLAS1M-24D3																																					
Dimensions	See diagram																																					
Standards																																						
	<table border="1"> <tr> <td>Standards compliance</td> <td colspan="2">IEC 61643-21 / EN 61643-21 / UL497A</td> </tr> </table>		Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																																		
Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																																					
	<table border="1"> <tr> <td>Certification</td> <td colspan="2">UL Listed</td> </tr> </table>		Certification	UL Listed																																		
Certification	UL Listed																																					
Part number																																						
	<table border="1"> <tr> <td>6415031</td> <td colspan="2"></td> </tr> </table>		6415031																																			
6415031																																						

