





# CITEL

## MSP-VM48-RINJ



- Security camera surge protector
- Combined POE Mid-Span Injector or Splitter and SPD
- Supports 802.3af, 802.3at, 802.3bt (POE++)
- Compact aluminum housing
- DIN Rail mounting or plate
- Integrated power supply injector connector (power supply separate)



G: Gas tube  
 D: Clamping diode network  
 V: Varistor  
 LED: Status indicator  
 L: Inductor

| Electrical Characteristics  |   |
|-----------------------------|---|
| Network                     | 48 Vac/Vdc                                  |
| Follow current              | If None                                     |
| Mechanical Characteristics  |   |
| SPD configuration           | 4 pairs                                     |
| Connection to Network       | By screw terminals: 2.5mm <sup>2</sup> max. |
| Format                      | DIN rail or flange                          |
| Mounting                    | DIN rail or plate (flange)                  |
| Housing material            | Anodized aluminum                           |
| Operating temperature       | Tu -40/+85°C                                |
| Protection rating           | IP20  |
| Voltage/operating indicator | Green Led ON                                |
| Disconnectors               |   |
| Thermal disconnecter        | Internal                                    |
| Back-up protection device   | Fuses type gG - 20A                         |
| Part number                 |   |
| 420455                      |   |

