


DACF15-10-440



- Type 2 (or 3) AC surge protector
- Interne Disconnection device
- Low caliber of the internal connector = systematic coordination with upstream circuit breaker
- In : 5 kA
- Imax : 15 kA
- Pluggable module for each phase
- Remote signaling option
- EN 61643-11, IEC 61643-11, UL1449 ed.5 compliance



Electrical Characteristics	
SPD type	2 (or 3)
Max. AC operating voltage	Uc 440 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 580 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 770 Vac disconnection
Residual Current Leakage current to Ground	Ipe < 1 mA
Follow current	If None
Nominal discharge current 15 x 8/20 μs impulses	In 5 kA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax 15 kA
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc 10 kV
Protection level @ In (8/20μs)	Up 1.5 kV
Admissible short-circuit current	Iscsr 100 000 A
Mechanical Characteristics	
Technology	MOV
SPD configuration	Single phase
Connection to Network	By screw terminals: 2.5-25mm ² (35mm ² rigid)
Format	Plug-in modular box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from AC network
Disconnection indicator	1 mechanical indicator - Red/Green
Spare module(s)	MDACF15-440
Remote signaling of disconnection	option DACF15S-10-440 : output on changeover contact
Wiring for remote signaling	1.5 mm ² max.
Dimensions	See diagram - 1TE (EN43880)
Weight	0.120 kg
Disconnectors	
Thermal disconnector	Internal
Installation ground fault breaker	Type 'S' or delayed
Back-up protection device	internal (equivalent AC rating : 25 A, gG Type)
Standards	
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Part number	
821310411	